

## E325PD-HDR 32" Pink LED TV




# Specification

LED Panel	
Aspect Ratio	Wide Screen 16:9
Auto Frame Rate	60 Hz
Brightness	250 cd/m2
Response Time	8ms (G-to-G)
Colors	16.7M
Lamp Life	50,000+ Hours
Viewing Angle	178º (Horizontal) / 178º (Vertical)
Display	
Active Screen Size	32" (31.5" Diagonal corner to corner)
Native Resolution	1366 x 768
Dynamic Contrast Ratio	5,000:1
Contrast Ratio	1,200 : 1 (Typical)
Features	
On Screen Display Control (OSD)	Picture, Sound, Channel, Parental, Setup, Others
Built-in Tuner	ATSC, NTSC, Clear QAM
OSD Supported Languages	English (Default), French, Spanish

Comb Filter3DDe-interface Technology3DAuto Dynamic Contrast ModeYesNoise ReductionYesMPEG Noise ReductionYesSurround Sound ModeYesSurround Sound ModeYesSurround Sound ModeYesSurround Sound HodeYesSurround Sound HodeYesSurround Sound HodeYesSurround Sound HodeYesSurround Sound HodeYesWall MountableYesSwirel Angles\$20P (Right & Left)Reck & Base DetachableYesFerergy GuideE32SLD-HDRInputs Adamp: OutputsYesHDMI (# of Ports & Version)3 x HDMISupported HDTV Signals1080/24p, 1080/60p, 10801, 720p, 480p, 4801Cable / Antenna Input1 x EC-Connector 750Supported HDTV Signals1080p.10801, 720p, 480p, 4801Supported VDPP) Input1 x Componet (Audio Input share with Composite)3.5 mm Headphone Jack (Juptul)1 x Componet Kubio Input share with Composite)3.5 mm Headphone Jack (Juptul)1 x CompositeMuschanized Kill1 (2 x RCA terminals (white, red)Mochanical Features <td< th=""><th>SCEPTRE®</th><th></th></td<>	SCEPTRE®	
De-interlace Technology     3D       Auto Dynamic Contrast Mode     Yes       Noise Reduction     Yes       Noise Reduction     Yes       Built-in Speakers     2 x 10W 8D       Surround Sound Mode     Yes       Sound Equalizer Settings     Yes (7-band)       Auto Volume Level Control     Yes       Wall Mountable     Yes       Swine Angles     ± 20° (Right & Left)       Swine Angles     ± 20° (Right & Left)       Swine K & Base Debachable     Yes       Energy Guide     E325LD-HDR       Inputs & Angles     ± 20° (Right & Left)       Sypported HDIV Signals     1080(740, 1080(760, 1080i, 720, 480, 480i       Cable / Antenna Input     1 x IEC-Connector 75Ω       Sypported HDIV Signals     1080(740, 1080(760, 1080i, 720, 480, 480i       Cable / Antenna Input     1 x IEC-Connector 75Ω       Sypported HDIV Signals     1080(7 600, 1080i, 720, 480, 480i       Cable / Antenna Input     1 x IEC-Connector 75Ω       Sypported HDIV Signals     1080 x 68 @ 60Hz (Natu-IS pin)       Card of POTS I     1 x Component (Audio input share with Composite)       Also XIG Go OUtput (L *	Weak Signal Enhancement	Yes
Auto Dynamic ContrastYesNoise ReductionYesMPEG Noise ReductionYesMPEG Noise ReductionYesBuillich SpaceAre2 x 10W 80Surround Sound ModeYesSurout Equalizer SettingsYes (7-band)Auto Volume Level ControlYesSwill MountableYesSwill MountableYesSwill MountableYesSwill MountableYesSwill MountableYesSwill Angles± 20° (Right 6 Left)Neek & Base DetachableYesEnergy GuideE32LD-HDRInputs Samp; Outputs1800/24p, 1080/60p, 1080i, 720p, 480p, 480iSupported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 750Supported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 750Supported HDV Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCardonent (YPbPr) Input1 x Component (Audio Input share with Composite)Sizmm Headphone Jeck (Output)1 x EPDIE Coaxial, Orange)VGA (# of Ports)1 x Component Evriminal (block)Supported HQAs Signals1360 x 768 @ 60Hz (Native & Max.) x 100 x 708 @ 60Hz x 1/> 200 mm x 100 mmVESA Mount Pattern (mm)200 mm x 100 mmVESA Mount Pattern (mm)200 mm x 100 mmVESA Mount Stand (Inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)<	Comb Filter	3D
Noise ReductionYesMPEG Noise ReductionYesBuilt-In Speakers2 x 10W 8QSound Equalizer SettingsYes (7-band)Auto Volume Level ControlYesWall MountableYesWall MountableYesWall MountableYesSound Equalizer SettingsYes (7-band)Neck & Base DetachableYesEnergy GuideE252LD-HDRInputs & Amp: OutputsE252LD-HDRInputs Asamp: Outputs1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDMI Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iCable / Antenna Input1 x IEC-Connector 75ΩSupported HDMI Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iCable / Antenna Input1 x IEC-Connector 75ΩSupported HDTV Signals1080p. 1080i, 720p. 480p. 480iCable / Antenna Input1 x IEC-Connector 75ΩSupported HDTV Signals1080p. 1080i, 720p. 480p. 480iSupported VDTV Input1 x Component (Audio input share with Composite)3 sm Headphone Jack (Output)1 x SDPIF (Caaxial, Orange)VGA (# of Ports)1 x L Supported VGA Signals1800 x 768 @ 60Hz < kr/>Supported VGA Signals1 x Composite (Native & Max )USB1 x LSB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mochanical Foatures29.05" x 3.42" x 17.32"VESA Mount Statern (mm)20.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Bax Di	De-interlace Technology	3D
MPEG Noise ReductionYesBuilt-in Speakers2 x 10W 8QSurround Sound ModeYesSound Equalizer SettingsYes (7-band)Auto Volume Level ControlYesWall MountableYesSwivel Angles± 20° (Right & Left)Neck & Base DetachableYesEnergy GuideE251D-HDRInputs & Samp Outputs1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDM Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDM Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDTV Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported VGA Signals1360 x 768 gi 60Hz (Native & Max )-chr />1280 x 720 gi 60Hz-chr />1280 x 600 gi 60Hz-chr /12024 x 768 gi 60Hz-chr />1280 x 720 gi 60Hz-chr />1280 x 600 gi 60Hz-chr /12024 x 768 gi 60Hz-chr />1280 x 600 gi 60HzVBS1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical Foatures2005 x 8.07* x 19.29*With Stand (Inches, W x H x D)2005 x 8.07* x 19.29*With Stand (Inches, W x H x D)20.05* x 8.27* x 17.32*Carton Box Dimension (inches, W x H x D)20.05* x 8.27* x 17.32*Weight with Stand (Ibs)13.20 Ibs.Rever20.05* x 8.27* x 19.29*<	Auto Dynamic Contrast Mode	Yes
Built-in Speakers2 × 10W 8ΩSurround Sound ModeYesSound Equalizer SettingsYes (7-band)Auto Volume Level ControlYesWall MountableYesSwivel Angles± 20ª (Right & Left)Neck & Base DetachableYesEnergy GuideE32SLD-HDRHDMU & Forts & Version)3 × HDMISupported HDMI Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDMI Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iCable / Antenna Input1 × IEC-Connector 75ΩSupported HDTV Signals1080/1080i, 720p. 480p. 480iSupported HDTV Signals1080/1080i, 720p. 480p. 480iSupported HDTV Signals1080/210p. 1080i, 720p. 480p. 480iSupported HDTV Signals1080/210p. 480p. 480iSupported HDTV Signals1080/20p. 480p. 480iSupported VDTV Signals1080/20p. 480eSupported VDTV Signals1080/20p. 480eSupported VGA Signals1080/20p. 480eSupported VGA Signals1080/20p. 486 @ 60Hz chtr />1280 x 720 @ 60Hz chtr />1280 x 600 @Supported VGA Signals10 200 mm x 100 mmVESA Mourt Pattern (mm)200 mm x 100 mmVESA Mourt Stard (inches, W x H x D)29.05* x 34.2* x 17.32*Carton Box Dimension (inches, W x H x D)29.05* x 34.2* x 17.32*Veight with Stand (luchs)13.20 ibs.Rotard Life with with Stand (luchs)13.20 ibs.Rores Rule (htt With Stand (luchs)13.20 ibs.Net Weight with Stand (luchs)13.20 ibs.Net Weight with Stand (luchs) <td< td=""><td>Noise Reduction</td><td>Yes</td></td<>	Noise Reduction	Yes
Surround Sound ModeYesSound Equalizer SettingsYes (7-band)Auto Volume Level ContolYesWall MountableYesSwivel Angles± 200 (Right & Left)Neck & Base DetachableYesEnergy GuideE252LD-HDRInputs & Ampi, OutputsHDMI (# of Ports & Version)3 x HDMISupported HDMI Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iCable / Antenna Input1 x IEC-Connector 75QSupported HDMI Signals1080p. 1080, 720p. 480p. 480iCable / Antenna Input1 x IEC-Connector 75QSupported HDTV Signals1080p. 1080, 720p. 480p. 480iComponent (YPbPr) Input1 x SPDIF (Caaxia), Orange)Stop of the MDM1 s SPDIF (Caaxia), Orange)Component (YPbPr) Input1 x Component (Audio input share with Composite)3 5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported HOTA Signals1600 x 768 @ 60Hz cbr />1280 x 720 @ 60Hz cbr />1280 x 600 @Composite Video1 x CompositeAnalog Audio Output (L + R)1 2 x RCA terminals (white, red)Mochanical Foature200mm x 100mmVESA Mourt Screw Size (mm)201m x 100mmVESA Mourt Stand (inches, W x H x D)29.05" x 8.07" x 17.32"Carlon Box Dimension (inches, W x H x D)29.05" x 8.07" x 17.32"Carlon Box Dimension (inches, W x H x D)29.05" x 8.07" x 17.32"Carlon Box Dimension (inches, W x H x D)29.05" x 8.07" x 17.32"Weight with Stand (lbs)13.20 lbs.Gross Weight (whis)13.20 lbs.<	MPEG Noise Reduction	Yes
Sound Equalizer SettingsYes (7-band)Auto Volume Level ControlYesWall MountableYesSwivel Angles± 20° (Right & Left)Nexck & Base DetachableYesEnergy GuideE325LD-HDRInputs & Samp: Outputs1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDM Signals1080/24p. 1080/60p. 1080i, 720p. 480p. 480iSupported HDV Signals1080p. 1080i, 720p. 480p. 480iSupported HDV Signals1080p. 1080i, 720p. 480p. 480iSupported HDV Signals150 SPDIF (Coaxial, Orange)VGA (# of Ports)1 x DS-USB terminal (blue.15 pin)Component (YPbPr) Input1 x Component (Audio input share with Composite)Som Headphone Jack (Output)1 x Eerphone terminal (black)Supported VGA Signals1360 x 768 @ 60HzSupported VGA Signals1 x CompositeAnalog Audio Output (L + R)1 (2 x CampositeAnalog Audio Output (L + R)20 00m x 100mmVESA Mount Strew Size (mm)29 05 * x 8.7* x 17.32"Carton Box Dimension (inches, W x H x D)29 05 * x 4.7* x 17.32"Carton Box Dimension (inches, W x H x D)29 05 * x 4.7* x 17.32"Carton Box Dimension (inches, W x H x D)29 05 * x 3	Built-in Speakers	2 x 10W 8Ω
Auto Volume Level ControlYesWall MountableYesSwivel Angles± 20° (Right & Left)Neck & Base DetachableYesEnergy GuideE325LD-HDRInputs & Samp; OutputsE325LD-HDRHDMI (# of Ports & Version)3 x HDMISupported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 75ΩSupported HDT Signals1080p, 1080i, 720p, 480p, 480iSupported VGA signals1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) x 1280 x 720 @ 60HzUSB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mochanical Features200mm x 100mmVESA Mount Sctere Size (mm)200mm x 100mmWESA Mount Sctere Size (mm)29.05* x 3.42* x 17.32*Carton Box Dimension (inches, W x H x D)29.05* x 3.42* x 17.32*With Stand (inches, W x H x D)29.05* x 3.42* x 17.32*Carton Box Dimension (	Surround Sound Mode	Yes
Wall MountableYesSwivel Angles± 20° (Right & Left)Neck & Base DetachableYesEnergy GuideB325LD-HDRInputs & Samp; Outputs3 x HDMISupported HDM Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 75QSupported HDT Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iSupported HDT Signals1080p, 1080i, 720p, 480p, 480iSupported HDT Signals1080p, 1080i, 720p, 480p, 480iSupported HDT Signals1 x EC-Connector 75QSupported HDT Signals1 x SDBI Erminal (blue,15 pin)Component (MPP) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) 1280 x 720 @ 60HzUSB1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical Features1WESA Mount Pattern (mm)200mm x 100mmVESA Mount Pattern (mm)29.05" x 8.07" x 19.29"With Stand (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Bax Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"Weight without Stand (lbs)13.20 lbs.Net Weight withstand (lbs)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs. <td>Sound Equalizer Settings</td> <td>Yes (7-band)</td>	Sound Equalizer Settings	Yes (7-band)
Swivel Angles± 20° (Right & Left)Neck & Base DetachableYesEnergy GuideE325LD-HDRInputs & Anny; OutputsHDMI (# of Ports & Version)3 x HDMISupported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iGable / Antenna Input1 x IEC-Connector 750Supported HDTV Signals1080p, 1080i, 720p, 480p, 480iSupported HDTV Signals1080p, 1080i, 720p, 480p, 480iSupported HDTV Signals1080p, 1080i, 720p, 480p, 480iSupported HDTV Signals1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue, 15 pin)Component (YPDPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.)-chr />1280 x 720 @ 60Hz-chr />1280 x 600 @ 60Hz-chr />1024 x 768 @ 60Hz-chr />800 x 600 @ 60HzUSB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mochanical FeaturesVersiteVESA Mount Pattern (mm)200mm x 100mmVESA Mount Strem (Size (mm)M 4 x 7mmDimensions29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 8.07" x 24.8"Weight11.320 lbs.Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)13.20 lbs.Weight without Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.Net Weigh	Auto Volume Level Control	Yes
Neck & Base DetachableYesEnergy GuideE325LD-HDRInputs & Aamp; OutputsBDBI (# of Ports & Version)3 x HDMISupported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 75QSupported HDTV Signals1080p, 1080i, 720p, 480p, 480iSPDIF Audio Output1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue.15 pin)Component (YPDPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported HVGA Signals1360 x 768 @ 60Hz (Native & Max.) 60Hz-cbr />1280 x 720 @ 60Hz-cbr />1280 x 600 @ 60Hz-cbr />1280 x 600 @ 60HzUSB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mcchanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Strew Size (mm)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 8.07" x 19.29"Weight11.95 lbs.Gross Weight without Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.PowerGross Weight (lbs)13.20 lbs.PowerConsumption (Typical)50W (Maximum), > 40W (Typical), > 1/> 40W (Typical), Power Consumption (Typical)50W (Maximum), <b< td=""><td>Wall Mountable</td><td>Yes</td></b<>	Wall Mountable	Yes
Energy Guide     E325LD-HDR       Inputs & amp; Outputs     Inputs & Version)     3 x HDMI       Supported HDMI Signals     1080/24p, 1080/60p, 1080i, 720p, 480p, 480i       Cable / Antenna Input     1 x IEC-Connector 75Ω       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       SPDIF Audio Output     1 x IEC-Connector 75Ω       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       SPDIF Audio Output     1 x IEC-Connector 75Ω       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       System Headphone Jack (Output)     1 x Component (Audio input share with Composite)       3.5mm Headphone Jack (Output)     1 x Earphone terminal (black)       Supported VGA Signals     1360 x 768 @ 60H2 (Native & Max.)     F>1280 x 720 @ 60H2     F>1280 x 600 @ 60H2       USB     1 x USB 2.0     12 x RCA terminals (white, red)     I2 x RCA terminals (white, red)       Mochanical Features     1 (2 x RCA terminals (white, red)     I2 x RCA terminals (white, red)       Mothant Stard (inches, W x H x D)     29.05" x 8.07" x 19.29"     IVIENT       With Stand (inches, W x H x D)     29.05" x 8.07" x 19.29"     IVIENT </td <td>Swivel Angles</td> <td>± 20º (Right &amp; Left)</td>	Swivel Angles	± 20º (Right & Left)
Inputs & amp; Outputs       HDMI (# of Ports & Version)     3 x HDMI       Supported HDMI Signals     1080/24p, 1080/60p, 1080i, 720p, 480p, 480i       Cable / Antenna Input     1 x IEC-Connector 75Ω       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       SPDIF Audio Output     1 x SPDIF (Coaxial, Orange)       VGA (# of Ports)     1 x D-SUB terminal (blue,15 pin)       Component (YPbPr) Input     1 x Component (Audio input share with Composite)       3.5mm Headphone Jack (Output)     1 x Earphone terminal (black)       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) 60Hz 1024 x 768 @ 60Hz 1280 x 700 @ 60Hz       SUSB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     VESA Mount Pattern (mm)       VESA Mount Screw Size (mm)     M4 x 7mm       Dimensions     29.05" x 8.07" x 19.29"       Without Stand (Inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     13.20 lbs.       Weight     19.20 lbs.	Neck & Base Detachable	Yes
HDMI (# of Ports & Version)     3 x HDMI       Supported HDMI Signals     1080/24p, 1080/60p, 1080i, 720p, 480p, 480i       Cable / Antenna Input     1 x IEC-Connector 75Q       Supported HDTV Signals     1080p, 1080i, 720p, 480p, 480i       Sypported HDTV Signals     1 x EC-Connector 75Q       Sypported HDTV Signals     1 x DSDIB terminal (blue,15 pin)       Component (YPbPr) Input     1 x Component (Audio input share with Composite)       3.5mm Headphone Jack (Output)     1 x Earphone terminal (blue,15 pin)       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) >1280 x 720 @ 60Hz >1280 x 600 @       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) >1280 x 600 @ 60Hz       USB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     200mm x 100mm       VESA Mount Pattern (mm)     29.05" x 8.0" x 19.29"       Without Stand (Inches, W x H x D)     29.05" x 8.0" x 19.29"       Without Stand (Inches, W x H x D)     29.05" x 8.7" x 24.8"       Weight     13.20 lbs.       Net Weight with Stand (lbs)     13.20 lbs.       Net Weight with Stand (lbs)	Energy Guide	E325LD-HDR
Supported HDMI Signals1080/24p, 1080/60p, 1080i, 720p, 480p, 480iCable / Antenna Input1 x IEC-Connector 75QSupported HDTV Signals1080p, 1080i, 720p, 480p, 480iSPDIF Audio Output1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue,15 pin)Component (YPbPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) br />1280 x 720 @ 60Hz 1280 x 600 @ 60Hz 200 @ 60Hz 1280 x 720 @ 60Hz 1280 x 600 @ 60Hz 1280 x 768 @ 60Hz 200 @ 60HzVGB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical Features200mm x 100mmVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensions29.05" x 8.07" x 19.29"Without Stand (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Power29.04 VAC, 50/60Hz, 3.04 (Max.)Power Consumption (Typical)50W (Maximum),Power Consumption (Typical)50W (Maximum),Power Consumption (Typical)50W (Maximum),Power Consumption (Typical)50W (Maximum),Power Consumption (Typical)	Inputs & Outputs	
Cable / Antenna Input1 x IEC-Connector 75ΩSupported HDTV Signals1080p, 1080i, 720p, 480p, 480iSPDIF Audio Output1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue,15 pin)Component (YPbPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) 60Hz 60Hz 1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical Features200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensions29.05" x 8.07" x 19.29"Without Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Weight1.32.0 lbs.Net Weight with Stand (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Net Weight (lbs)1.2.9 (bfur, 3.0.4 (Max.)Power29.05" x 8.07" x 19.40W (Max.)Power Consumption (Typical)50W (Maximum), > />40W (Arguical),  S0W (Maximum),  S0W (Maximum),  S0W (Maximum),  S0W (Maximum),  S0W (Maximum),  S0W (Maximum),  S0W (Maximum), S0W (Max	HDMI (# of Ports & Version)	3 x HDMI
Supported HDTV Signals1080p, 1080i, 720p, 480p, 480iSPDIF Audio Output1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue, 15 pin)Component (VPbPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) 60Hz br />1024 x 768 @ 60Hz br />1024 x 768 @ 60Hz br />800 x 600 @ 60HzUSB1 x USB 2.0Composite Video1 x Composite 1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mm VESA Mount Screw Size (mm)With Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (inches, W x H x D)29.05" x 3.42" x 17.32" Carton Box Dimension (inches, W x H x D)Net Weight with Stand (lbs)13.20 lbs.Net Weight (lbs)19.50 lbs.Gross Weight (lbs)19.50 lbs.Power19.52 lbs.Power Consumption (Typical)100 - 240 VAC, 50/60Hz, 3.04 (Max.)Power Consumption (Typical)50W (Maximum), br />40W (Typical), br />40W (Typical)	Supported HDMI Signals	1080/24p, 1080/60p, 1080i, 720p, 480p, 480i
SPDIF Audio Output1 x SPDIF (Coaxial, Orange)VGA (# of Ports)1 x D-SUB terminal (blue,15 pin)Component (YPbPr) Input1 x Component (Audio input share with Composite)3.5mm Headphone Jack (Output)1 x Earphone terminal (black)Supported VGA Signals1360 x 768 @ 60Hz (Native & Max.) >1280 x 720 @ 60Hz >1280 x 600 @ 60HzUSB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWithout Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"Weight13.20 lbs.Net Weight with Stand (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Net Weight (lbs)13.20 lbs.Power19.240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), >40W (Typical), >40W (Typical), >40W (Typical), >40W (Typical), >40W (Typical), 50W (Maximum), >40W (Typical), 50W (Typical), 50W (Maximum), 50W (Typical), 50W	Cable / Antenna Input	1 x IEC-Connector 75Ω
VGA (# of Ports)     1 x D-SUB terminal (blue,15 pin)       Component (YPbPr) Input     1 x Component (Audio input share with Composite)       3.5mm Headphone Jack (Output)     1 x Earphone terminal (black)       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) 1280 x 720 @ 60Hz 1280 x 600 @ 60Hz       SUB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     200mm x 100mm       VESA Mount Pattern (mm)     200mm x 100mm       VESA Mount Pattern (xm)     29.05" x 8.07" x 19.29"       With Stand (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     29.05" x 3.42" x 17.32"       Without Stand (lbs)     1.3.20 lbs.       Net Weight with Stand (lbs)     1.3.20 lbs.       Net Weight without Stand (lbs)     1.9.5 lbs.       Gross Weight (lbs)     1.9.2 lbs.       Power     240 VAC, 50/60Hz, 3.0A (Max.)       Power Consumption (Typical)     50W (Maximum), 40W (Typical), 5 x 1W (Standby)	Supported HDTV Signals	1080p, 1080i, 720p, 480p, 480i
Component (YPbPr) Input     1 x Component (Audio input share with Composite)       3.5mm Headphone Jack (Output)     1 x Earphone terminal (black)       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) < br />1280 x 720 @ 60Hz < br />1280 x 600 @ 60Hz < br />1280 x 600 @ 60Hz       USB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     1 (2 x RCA terminals (white, red)       VESA Mount Pattern (mm)     200mm x 100mm       VESA Mount Screw Size (mm)     M4 x 7mm       Dimensions     29.05" x 8.07" x 19.29"       Without Stand (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     29.05" x 2.48"       Weight     1.320 lbs.       Net Weight with Stand (lbs)     13.20 lbs.       Ross Weight (lbs)     1.95 lbs.       Gross Weight (lbs)     1.95 lbs.       Power     1.92 VAC, 50/60Hz, 3.0A (Max.)       Power Consumption (Typical)     50W (Maximum), > />40W (Typical), 5 41W (Standby)	SPDIF Audio Output	1 x SPDIF (Coaxial, Orange)
3.5mm Headphone Jack (Output)     1 x Earphone terminal (black)       Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) 1280 x 720 @ 60Hz 1280 x 600 @       SUBPORTED VIGA Signals     1360 x 768 @ 60Hz (Native & Max.) 1280 x 600 @ 60Hz       USB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     VESA Mount Pattern (mm)       VESA Mount Screw Size (mm)     M4 x 7mm       Dimensions     200mm x 100mm       Without Stand (inches, W x H x D)     29.05" x 8.07" x 19.29"       Without Stand (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     13.20 lbs.       Net Weight with Stand (lbs)     13.20 lbs.       Ross Weight (lbs)     13.20 lbs.       Net Weight without Stand (lbs)     11.95 lbs.       Gross Weight (lbs)     13.20 lbs.       Power     240 VAC, 50/60Hz, 3.0A (Max.)       Power Consumption (Typical)     50W (Maximum), >40W (Typical), <<1W (Standby)	VGA (# of Ports)	1 x D-SUB terminal (blue,15 pin)
Supported VGA Signals     1360 x 768 @ 60Hz (Native & Max.) 1280 x 720 @ 60Hz 1280 x 600 @ 60Hz 1280 x 708 @ 60Hz 800 x 600 @ 60Hz       USB     1 x USB 2.0       Composite Video     1 x Composite       Analog Audio Output (L + R)     1 (2 x RCA terminals (white, red)       Mechanical Features     200mm x 100mm       VESA Mount Pattern (mm)     200mm x 100mm       VESA Mount Screw Size (mm)     M4 x 7mm       Dimensions     29.05" x 8.07" x 19.29"       Without Stand (inches, W x H x D)     29.05" x 3.42" x 17.32"       Carton Box Dimension (inches, W x H x D)     29.05" x 3.42" x 17.32"       Weight     13.20 lbs.       Net Weight with Stand (lbs)     13.20 lbs.       Net Weight without Stand (lbs)     11.95 lbs.       Gross Weight (lbs)     18.26 lbs.       Power     Power Kange (V, A, Hz)       Power Range (V, A, Hz)     100 - 240 VAC, 50/60Hz, 3.0A (Max.)       Power Consumption (Typical)     50W (Maximum), 400W (Typical), 	Component (YPbPr) Input	1 x Component (Audio input share with Composite)
60Hz 1024 x 768 @ 60Hz 800 x 600 @ 60HzUSB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"WeightWithout Stand (lbs)Net Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)1.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPowerPower Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	3.5mm Headphone Jack (Output)	1 x Earphone terminal (black)
USB1 x USB 2.0Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"WeightWeightNet Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPowerPower Consumption (Typical)50W (Maximum), st />40W (Typical), st />>40W (Typ	Supported VGA Signals	1360 x 768 @ 60Hz (Native & Max.) 1280 x 720 @ 60Hz 1280 x 600 @
Composite Video1 x CompositeAnalog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"WeightVESAWeight13.20 lbs.Net Weight with Stand (lbs)13.20 lbs.Net Weight (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPowerPower Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), <dw (typical),<br=""></dw> < 1W (Standby)		60Hz 1024 x 768 @ 60Hz 800 x 600 @ 60Hz
Analog Audio Output (L + R)1 (2 x RCA terminals (white, red)Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensions29.05" x 8.07" x 19.29"With Stand (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 3.42" x 17.32"WeightVeightWeight13.20 lbs.Net Weight with Stand (lbs)13.20 lbs.Stare See See See See See See See See See S	USB	1 x USB 2.0
Mechanical FeaturesVESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 8.07" x 24.8"WeightWeightNet Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPower Range (V, A, Hz)Power Consumption (Typical)50W (Maximum), >40W (Typical), >40W (Typical), >40W (Typical), >40W (Typical),	Composite Video	1 x Composite
VESA Mount Pattern (mm)200mm x 100mmVESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)29.05" x 8.7" x 24.8"Weight35.1" x 8.7" x 24.8"Weight13.20 lbs.Net Weight without Stand (lbs)13.20 lbs.In EV Weight (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.Power18.26 lbs.Power Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), b />40W (Typical), b />5 1W (Standby)	Analog Audio Output (L + R)	1 (2 x RCA terminals (white, red)
VESA Mount Screw Size (mm)M4 x 7mmDimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)35.1" x 8.7" x 24.8"Weight35.1" x 8.7" x 24.8"Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.Power100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), > 40W (Typical), < 1W (Standby)	Mechanical Features	
DimensionsWith Stand (inches, W x H x D)29.05" x 8.07" x 19.29"Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)35.1" x 8.7" x 24.8"Weight35.1" x 8.7" x 24.8"Weight with Stand (lbs)13.20 lbs.Net Weight with Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPower Range (V, A, Hz)Power Consumption (Typical)100 - 240 VAC, 50/60Hz, 3.0A (Max.)SOW (Maximum), 400 (Typical), < 1W (Standby)	VESA Mount Pattern (mm)	200mm x 100mm
With Stand (inches, W x H x D)   29.05" x 8.07" x 19.29"     Without Stand (Inches, W x H x D)   29.05" x 3.42" x 17.32"     Carton Box Dimension (inches, W x H x D)   35.1" x 8.7" x 24.8"     Weight   35.1" x 8.7" x 24.8"     Weight   13.20 lbs.     Net Weight with Stand (lbs)   13.20 lbs.     Net Weight without Stand (lbs)   11.95 lbs.     Gross Weight (lbs)   18.26 lbs.     Power   100 - 240 VAC, 50/60Hz, 3.0A (Max.)     Power Consumption (Typical)   50W (Maximum), >40W (Typical), > 1W (Standby)	VESA Mount Screw Size (mm)	M4 x 7mm
Without Stand (Inches, W x H x D)29.05" x 3.42" x 17.32"Carton Box Dimension (inches, W x H x D)35.1" x 8.7" x 24.8"WeightWeightNet Weight with Stand (Ibs)13.20 lbs.Net Weight without Stand (Ibs)11.95 lbs.Gross Weight (Ibs)18.26 lbs.PowerPower Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	Dimensions	
Carton Box Dimension (inches, W x H x D)35.1" x 8.7" x 24.8"WeightWeight35.1" x 8.7" x 24.8"Net Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.Power100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	With Stand (inches, $W \times H \times D$ )	29.05" x 8.07" x 19.29"
WeightNet Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPower Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	Without Stand (Inches, W x H x D)	29.05" x 3.42" x 17.32"
Net Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPower Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	Carton Box Dimension (inches, W x H	x D)35.1" x 8.7" x 24.8"
Net Weight with Stand (lbs)13.20 lbs.Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.PowerPower Range (V, A, Hz)100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)	Weight	
Net Weight without Stand (lbs)11.95 lbs.Gross Weight (lbs)18.26 lbs.Power100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)		13.20 lbs.
Gross Weight (lbs)18.26 lbs.Power100 - 240 VAC, 50/60Hz, 3.0A (Max.)Power Consumption (Typical)50W (Maximum), 40W (Typical), < 1W (Standby)		
Power     Power Range (V, A, Hz)     100 - 240 VAC, 50/60Hz, 3.0A (Max.)     Power Consumption (Typical)     50W (Maximum), 40W (Typical), < 1W (Standby)	Gross Weight (lbs)	
Power Consumption (Typical) 50W (Maximum), 40W (Typical), < 1W (Standby)	Power	
Power Consumption (Typical) 50W (Maximum), 40W (Typical), < 1W (Standby)	Power Range (V, A, Hz)	100 - 240 VAC, 50/60Hz, 3.0A (Max.)
	Power Consumption (Typical)	
	Regulations / Certifications	

SCEPTRE®	
Certificates	FCC, cTUVus, Energy Star V6.1, ISTA 3A
Warranty	
Limited Parts and Labor	One Year





#### LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



#### HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.



#### **Coaxial Digital Out**

Offering superior backwards compatibility for stereo receivers. This Sceptre TV is equipped with a Coaxial Digial audio output which will enrich your TV audio experience with the coaxial supported soundbar, soundbase or audio equipment.



#### USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



#### DTS SRS TruSurround HD

DTS SRS TruSurround HD delivers an enveloping combination of smooth treble and maximum bass response. The broad sound capability produces dialog that is crisp and audible.



#### **Customer Service**

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.





### **30+ Years of Experience**

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.