

E555BV-FMQR 55" LED TV



Specification

Display		
Active Screen Size	54.6" Diagonal Viewable	
Native Resolution	1920 x 1080	
Refresh Rate	Up to 60Hz Refresh Rate	
Aspect Ratio	16:9	
Response Time	8 ms (G-to-G)	
Dynamic Contrast Ratio	1,000,000:1	
Color Depth	16.7 Million	
Contrast Ratio	10,000:1	
Brightness (Typ.)	280cd/m²	
Viewing Angle	Vertical: 178° / Horizontal: 178°	
Backlight Life	50,000+ Hours	
Features		
On Screen Display Control (OSD)	Picture, Sound, Channel, Setup	
Color Temperature	Warm, Normal, Cool, Standards	
Adjustable Picture Control*	Brightness, Contrast, Backlight, Color, Tint, Sharp	
Picture Presets	Normal, Wide, Cinema, Zoom	

Built-in Tuner	ATSC / NTSC
OSD Supported Languages	English (Default), Spanish, French, Chinese
Weak Signal Enhancement	Yes
Comb Filter	3D
De-interlace Technology	3D
Auto Dynamic Contrast Mode	Yes
Noise Reduction	Yes
MPEG Noise Reduction	Yes
Surround Sound Mode	SRS TruSurround HD
Sound Equalizer Settings	5-Band
Auto Volume Level Control	Yes
Wall Mountable	Yes
Neck & Base Detachable	Yes
Energy Guide	V6.1
Audio Features	
Speakers	10 watts per Channel x 2
Video Features	
White Balance	Available
Outputs	
Analog Audio Output (L + R)	1 (2 × RCA terminals (white, red))
Headphone Output	1 × Earphone terminal (black)
Inputs	
PC Audio In	1 x Audio in terminal (Black)
Inputs & amp; Outputs	
HDMI (# of Ports & Version)	3
	-
Supported HDMI Signals	1080/24p, 1080/60p,1080i, 720P, 480p,480i
Supported HDMI Signals Cable / Antenna Input	1080/24p, 1080/60p,1080i, 720P, 480p,480i 1 x IEC-Connector 75 Ohm
Cable / Antenna Input	1 × IEC-Connector 75 Ohm
Cable / Antenna Input Supported HDTV Signals	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black)
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports)	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin)
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite 1920 x 1080@ 60Hz (Native & Max) < br /> 1600 x 900 < br /> 1366 x 768 < br /> 1280 x
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility VGA Input Support	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite 1920 x 1080@ 60Hz (Native & Max) < br /> 1600 x 900 < br /> 1366 x 768 < br /> 1280 x
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility VGA Input Support Mechanical Features	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite 1920 × 1080@ 60Hz (Native & Max) < br /> 1600 × 900 < br /> 1366 × 768 < br /> 1280 × 1024 < br /> 800 × 600
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility VGA Input Support Mechanical Features VESA Mount Screw Size (mm)	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite 1920 × 1080@ 60Hz (Native & Max) < br /> 1600 × 900 < br /> 1366 × 768 < br /> 1280 × 1024 < br /> 800 × 600
Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video HDTV Signal Compatibility VGA Input Support Mechanical Features VESA Mount Screw Size (mm) Dimensions	1 × IEC-Connector 75 Ohm 1080p, 1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) 1 × D-SUB terminal (blue, 15 pin) 1 × Component 1 × USB 2.0 1 × Composite 1920 × 1080@ 60Hz (Native & Max) 1024 br />800 × 600 Upper two: M6 × 18mm; Bottom two: M6 × 32mm

SCEPTRE®		
Weight		
Net Weight with Stand (lbs)	51.59 lbs	
Net Weight without Stand (lbs)	40.5 lbs	
Gross Weight (lbs)	63.71 lbs	
Power		
Power Range (V, A, Hz)	100 - 240VAC, 50/60Hz, 3.0A (Max.)	
Power Consumption (Typical)	88W (Typical) ≤ 1W (Standby)	
Regulations / Certifications		
Certificates	cTUVus, FCC, Energy Star, ISTA 3A, SRS TruSurround HD	
Warranty		
Limited Parts and Labor	1 Year	
What's in the Box?		

href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-142021"


270010 C-product 745 category 19 category 69. html">142021270010 C-/a>

<a

Remote Control Model No



Key Features





LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.

HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.

Coaxial Digital Out

Offering superior backwards compatibility for stereo receivers. This Sceptre TV is equipped with a Coaxial Digial audio output which will enrich your TV audio experience with the coaxial supported soundbar, soundbase or audio equipment.







USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.

DTS SRS TruSurround HD

DTS SRS TruSurround HD delivers an enveloping combination of smooth treble and maximum bass response. The broad sound capability produces dialog that is crisp and audible.

Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



Key Features



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.