

X325BV-FMQC 32" LED TV



Specification

Display	
Active Screen Size	31.5" Diagonal Viewable
Native Resolution	1920 x 1080
Refresh Rate	MEMC 120
Aspect Ratio	16:9
Response Time	8 ms (G-to-G)
Dynamic Contrast Ratio	1,000,000:1
Color Depth	16.7M (8-bit)
Contrast Ratio	3,000:1
Brightness (Typ.)	280 cd/m²
Viewing Angle	178º (Horizontal) / 178º (Vertical)
Backlight Life	30,000+ Hours
Features	
On Screen Display Control (OSD)	Picture, Sound, Channel, Parental, Setup, Others
Color Temperature	Warm, Normal, Cool, Standards
Support MHL	Yes
Adjustable Picture Control*	Brightness, Contrast, Backlight, Color, Tint, Sharp


SCEPTRE®	
Built-in Tuner	ATSC / NTSC
OSD Supported Languages	English (Default), French, Spanish
Weak Signal Enhancement	Yes
Comb Filter	3D
De-interlace Technology	3D
Auto Dynamic Contrast Mode	Yes
Noise Reduction	Yes
MPEG Noise Reduction	Yes
Surround Sound Mode	Yes
Sound Equalizer Settings	Yes (5-band)
Auto Volume Level Control	Yes
Wall Mountable	Yes
Swivel Angles	30º (Left & Right)
Neck & Base Detachable	Yes
Energy Guide	Yes
Audio Features	
Speakers	2 ×10W/8Ω
HDTV Signal Compatibility	
VGA Input Support	1920 x 1080 (Native & Max)
vo.v.iiipat sapport	1360 x 768
	1280 x 1024
	10/4 x /08
	1024 x 768 800 x 600
Inputs & Dutputs	1024 x 768 800 x 600
Inputs & Dutputs HDMI (# of Ports & Version)	800 x 600
HDMI (# of Ports & Version)	800×600 3 × HDMI (only HDMI2 with MHL function)
HDMI (# of Ports & Version) Supported HDMI Signals	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input	800×600 $3 \times \text{HDMI (only HDMI2 with MHL function)}$ $1080/24\text{p, }1080/60\text{p, }1080\text{i, }720\text{p, }480\text{p, }480\text{i}$ $1 \times \text{IEC-Connector }75\Omega$
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black)
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 x Coaxial (Orange)
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 x Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin)
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input	3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite)
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 x Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin)
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output)	3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R) Mechanical Features	3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite 1 (2 × RCA terminals (white, red))
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R) Mechanical Features VESA Mount Pattern (mm)	3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite 1 (2 × RCA terminals (white, red))
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R) Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite 1 (2 × RCA terminals (white, red))
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R) Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite 1 (2 × RCA terminals (white, red)) 200mm × 200mm Upper two: M6 × 18mm, Bottom two: M6 × 28mm
HDMI (# of Ports & Version) Supported HDMI Signals Cable / Antenna Input 3.5mm Auxiliary Input Jack Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input 3.5mm Headphone Jack (Output) USB Composite Video Analog Audio Output (L + R) Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm)	800 x 600 3 × HDMI (only HDMI2 with MHL function) 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75Ω 1 × PC Audio in terminal (black) 1080p,1080i, 720p, 480p, 480i 1 × SPDIF (Optical, Black) or 1 × Coaxial (Orange) 1 × D-SUB terminal (Blue, 15 pin) 1 × Component (Audio input share with composite) 1 × Earphone terminal (black) 1 × USB 2.0 1 × Composite 1 (2 × RCA terminals (white, red))



Carton Box Dimension (inches, W x H $\scriptstyle\rm X$	D)31.89" x 20.67" x 6.69"
Weight	
Net Weight with Stand (lbs)	9.75 lbs
Net Weight without Stand (lbs)	9.35 lbs
Gross Weight (lbs)	14.52 lbs
Power	
Power Range (V, A, Hz)	100 - 240VAC, 50/60Hz, 1A (Max)
Power Consumption (Typical)	50 W (Max)
	28 W (Typical)
	≤0.5 W (Standby)
Regulations / Certifications	
Energy Star	V7.0
Certificates	cETLus, FCC, Energy Star, ISTA 3A
Compliances	HDMI, MHL
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Remote Control Model No	<a< td=""></a<>
	href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-142021
	270010C-product745category19category69.html" >142021270010C



Key Features



LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.



Coaxial Digital Out

Offering superior backwards compatibility for stereo receivers. This Sceptre TV is equipped with a Coaxial Digial audio output which will enrich your TV audio experience with the coaxial supported soundbar, soundbase or audio equipment.



USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.