

X322WV-MQR 32" LED HDTV



Specification

Display	
Active Screen Size	31.5" Diagonal Viewable
Panel Type	IPS (In-Plane Switching)
Native Resolution	1366 x 768
Refresh Rate	60Hz
Aspect Ratio	16:9
Response Time	8 ms (G-to-G)
Pixel Pitch	0.51075mm (H) x 0.51075mm (V)
Dynamic Contrast Ratio	1,000,000:1
Color Gamut	sRGB: 81% DCI-P3: 67%
Color Depth	16.7M (8bits-true)
Contrast Ratio	3,000:1
Brightness (Typ.)	250 cd/m²
Viewing Angle	178º (Horizontal) / 178º (Vertical)
Backlight Life	50,000+ Hours
Surface Treatment	Antiglare (Haze 1%), Hard coating (3H)
Features	

On Screen Display Control (OSD)	Picture, Sound, Channel, Setup
Color Temperature	Warm, Normal, Cool, Standards
Adjustable Picture Control*	Brightness, Contrast, Backlight, Color, Tint, Sharp
Picture Presets	Normal, Wide, Cinema, Zoom
Built-in Tuner	ATSC / NTSC
OSD Supported Languages	English (Default), Spanish, French, Chinese
Weak Signal Enhancement	Yes
Comb Filter	3D
De-interlace Technology	3D
Auto Dynamic Contrast Mode	Yes
Noise Reduction	Yes
MPEG Noise Reduction	Yes
Surround Sound Mode	Yes
Sound Equalizer Settings	Yes
Auto Volume Level Control	Yes
Wall Mountable	Yes
Swivel Angles	25° (Left & Right)
Neck & Base Detachable	Yes
Energy Guide	Yes

#### Audio Features

Speakers	2 × 10W/8Ω
----------	------------

#### Video Features

White Balance	Available
---------------	-----------

#### Inputs & Outputs

HDMI (# of Ports & Version)	3 × HDMI
Supported HDMI Signals	1080/24p, 1080/60p, 1080i, 720p, 480p, 480i
Cable / Antenna Input	1 × IEC-Connector 75Ω
3.5mm Auxiliary Input Jack	1 × Audio in terminal (black)
Supported HDTV Signals	1080p, 1080i, 720p, 480p, 480i
SPDIF Audio Output	1 × SPDIF (Optical, Black)
VGA (# of Ports)	1 × D-SUB terminal (Blue, 15 pin)
Component (YPbPr) Input	x1 Component
3.5mm Headphone Jack (Output)	1 × Earphone terminal (black)
Supported VGA Signals	1360 x 768 @ 60Hz (Native & Max.) 1280 x 1024 @ 60Hz 1024 x 768 @ 60Hz 800 x 600 @ 60Hz
USB	1 × USB 2.0
Composite Video	1 × Composite
Analog Audio Output (L + R)	x 1

#### Mechanical Features

VESA Mount Pattern (mm)	200mm x 100mm
VESA Mount Screw Size (mm)	M4 x 6mm

Dimensions	
With Stand (inches, W x H x D)	29.1" x 19.3" x 8.1"
Without Stand (Inches, W x H x D)	29.1" x 17.3" x 3.5"
Carton Box Dimension (inches, W x H x D)	33.1" x 21.8" x 6.7"
Weight	
Net Weight with Stand (lbs)	12.32 lbs
Net Weight without Stand (lbs)	9.9 lbs
Gross Weight (lbs)	17.16 lbs
Power	
Power Range (V, A, Hz)	100 - 240VAC, 50/60Hz, 3A (Max)
Power Consumption (Typical)	40 W (Typical)
Maximum	65 W
Standby	≤1 W (Standby)
Regulations / Certifications	
Regulations	cTUVus, FCC, ISTA 3A
Certifications	Energy Star 7.0, HDMI
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Remote Control Model No	<a href="https://www.sceptre.com/Accessories/Remote-Control/TV-RC-142022370010C-product751category19category69.html?search=142022370010C" target="_blank">142022370010C</a>

## Key Features



### LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



### HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.



### Coaxial Digital Out

Offering superior backwards compatibility for stereo receivers. This Sceptre TV is equipped with a Coaxial Digital audio output which will enrich your TV audio experience with the coaxial supported soundbar, soundbase or audio equipment.



### USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



### Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



### 30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.