

# U508CV-UMKC 50" 4K UHD TV



# Specification

Display	
Active Screen Size	48.5" Diagonal Viewable
Panel Type	IPS (In-Plane Switching)
Native Resolution	3840 x 2160
Refresh Rate	60Hz
Aspect Ratio	16:9
Display Colors	1.07G (10-bit)
Response Time	9 ms (G-to-G)
Pixel Pitch	0.27963mm (H) x 0.27963mm (V)
Dynamic Contrast Ratio	1,000,000:1
Color Gamut	sRGB: 82% DCI-P3: 67%
Contrast Ratio	3,000:1
Brightness (Typ.)	250 cd/m <sup>2</sup>
Viewing Angle	Vertical: 178° / Horizontal: 178°
Backlight Type	LED
Backlight Life	30,000+ Hours
Surface Treatment	Antiglare (Haze 1%), Hard coating (3H)


SCEPTRE®		
Audio Features		
Auto Volume Level Control	AVL available	
Audio Adjustable Control	Treble, Bass, Balance, Volume, Mute control, Preset EQ	
Speakers	2 x 10W/8Ω	
Equalizer Settings	5-band	
Surround Sound Mode	Available	
Highlight Features		
True Ultra High Definition 4k x 2k	3840 x 2160	
Display		
HDCP Version	2.2 (Specifically design for 4k video)	
HDMI 2.0	Support latest Standard for 4k x 2k video at 60Hz input signal.	
CEC & ARC	Available	
Video Features		
OSD (On Screen Display Control)	Picture, Sound, Channel, Setup	
Picture Mode	Normal / Wide / Cinema / Zoom	
Picture Control	Brightness, Contrast, Backlight, Color, Tint, Sharpness	
Temperature (color)	Warm / Normal / Cool / Standards	
White Balance	Adjustable. Multiple Preset Options available.	
OSD Supported Languages / Subtitles	English / Spanish / French	
Other Features		
Show/Hide Channel	Available	
Built-in Tuner	ATSC / NTSC	
Weak Signal Enhancement	Equipped	
Energy Guide	Link to Energy Guide Label	
Comb Filter	3D	
De-interlace Technology	3D	
Noise Reduction	Equipped	
Second Audio Program (SAP)	Available	
User Define Channel Label	Available	
Closed Captioning (CC)	Available	
Program Guide	Available	
Parental Control (V-Chip)	USA & Canada	
Digital Clock	Equipped	
Sleep Timer	Available	
Channel Block (with passcode)	Analog & Digital	
Power Saving Mode	Available	
Users Define Source Name	Available	
Inputs & Outputs		
HDMI (# of Ports & Version)	4 x HDMI	
	(HDMI1: HDMI2.0, HDCP 2.2, CEC;	
	HDMI 2: HDMI2.0, HDCP 2.2, CEC;	
	HDMI 3: HDMI2.0, HDCP 2.2, CEC;	
	HDMI 4: HDMI1.4, ARC, CEC)	

Supporder HDMI signals4.k 1080/24p, 1080/690, 1080, 720p, 480Cable / Antenna Input1.k EC-connector 75 OhmSupporder HDVI Signals1080, 1200, 480SUPDIF Audio Output1.x SPDIF (Optical, Black)USB1.x SPDIF (Optical, Black)Composite Video1.x SPDIF (Optical, Black)Composite Video1.x SPDIF (Optical, Black)Composite Video1.x SPDIF (Optical, Black)Mated Supported HDVI2.x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)Mated Supported HDVISearch State White, Red)) via Mini Line Out jack (Cable not included)Supported HDVISearch State MatheSund DetachableYesSund DetachableCapableSund DetachableCapableSund DetachableCapableSeare State Seare Se	SCEPTRE®	
Supported HDTV Signals1080p. 1080i, 720p. 480p. 480iSPDF Audio Output1 x SPDF (Optical, Black)USB1 x USB 2.0Composite Video1 x Composte (Video and Audio ports share with Component)Analog Audio Output (L + R)1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)Macharical FoaturesBlack HousingStand TypeMatted-Frished MetalWall MountableYesWall MountableCapaleStand DepaMatted-Frished MetalStand DepaMatted-Frished MetalStand DepakableCapaleBase DataAbleCapaleBase DataAbleYesStand Deta(min)400mm x 200mnBase DataAbleYesStand Screw Size & Quantity (mm)44 x 14mm (4pcs)DimensionsVesWith Stand (Inches, W x H x D)43 4 x x 27.5" x 9.5"Without Stand (Inches, W x H x D)43 4 x x 25.2" x 3.2"Carton Bas Dimension (Inches, W x H X D)43 4 x x 25.2" x 3.2"WeightVesWeight with Stand (Ibs)2.0 IbsGross Weight (Ibs)3.2 JosPower Ange (V, A, Iz)100 - 240VAC, 6050Hz, 2A (Max.)Power Range (V, A, Iz)100 - 240VAC, 6050Hz, 2A (Max.)Power Range (V, A, Iz)100 - 240VAC, 6050Hz, 2A (Max.)Royalistics / Cartifications4 100 - 240VAC, 6050Hz, 2A (Max.)Royalistics / Cartifications6 100 - 240VAC, 6050Hz, 2A (Max.)Royalistics / Cartifications6 100 - 240VAC, 6050Hz, 2A (Max.)Royalistics / Cartifications6 100 -	Supported HDMI Signals	4K, 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i
SPDF Audo Output1 x SPD/F (Optical, Black)USB1 x USB 2.0Composite Video1 x Composite (Wideo and Audio ports share with Component)Analog Audio Output (L + R)1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cabie not included)Mechanical FeaturesElect HousingStand TypeMatted-Finished MetalWall MountableYesWall Mount Screw Size (mm)M6 x 9mmStand TypeOpt, Left and Right: 0.48"; Bottom: 0.85"Wall Mount Screw Size (mm)400mm x 200mmBase ElecthableYesStand DetachableYesStand Screw Size & Quantity (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)43.4" x 27.5" x 9.5"With Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"With Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)43.4" x 25.2" x 3.2"Net Weight with Stand (Ibs)22.0 IbsNet Weight with Stand (Ibs)20.9 IbsGross Weight (Ibs)35.2 IbsPowerPowerPower Consumption (Typical)73WMaxium5160WStandby6.0 SWStandby6.0 SWRegulations / CortificationsHDMIWarium5160WStandby6.0 SWStandby6.0 SWPower Consumption (Typical)73WMaxium5.0 SWStandby6.0 SWWarium Ku <td>Cable / Antenna Input</td> <td>1 x IEC-connector 75 Ohm</td>	Cable / Antenna Input	1 x IEC-connector 75 Ohm
USB1 x USB 2.0Composite Video1 x Composite (Video and Audio ports share with Component)Analog Audio Output (L + R)1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)Mechanical FeaturesViesStand TypeMatted-Finished MetalWall MountableYesWall MountableCapableBeeel WithTop. Left and Right: 0.48"; Bottom: 0.85"Sim DesignUitra SimVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Storew Size & Quantity (mm)41.4" x 27.5" x 9.5"With Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)43.4" x 25.2" x 3.2"Withstand (Inches, W x H x D)2.0 lbsRever Weight with Stand (Ibs)2.0 lbsStand Stand Stand (Inches, W x H x D)3.2 lbsPowerVesWaightVesRever Gauge (V, A, Hz)7.3WPower Amage (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Amage (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Cartifications100 - 240VAC, 60/50Hz, 2A (Max.)Regulations / Certifications100 - 240VAC, 60/50Hz, 2A (Max.) <trr></trr>	Supported HDTV Signals	1080p, 1080i, 720p, 480p, 480i
Composite Video1 x Composite (Video and Audio ports share with Component)Analog Audio Output (L + R)1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)Mechanical FeaturesExact Stand TypeChassis ColorsBlack HousingStand TypeMatted-Finished MetalWall MountableYesWall Mount Screw Size (mm)M6 x 9mmStand DetachableCapableBezel WidthTop. Left and Right: 0.48" ; Bottom: 0.85"Sim DesignUltra SlimVESA Mount Pattern (mn)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)YesDimensionsYesWith Stand (inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (inches, W x H x D)43.4" x 27.5" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"VeightVeight with Stand (lbs)20.9 lbsGross Weight (lbs)3.2 lbsPowerSo 2.0 lbsPower Consumption (Typical)3WAnaumans 160WStandbys 5.9WRegulations / CertificationsHDMIWarrantyIndifWarrantyIndifWarrantyIndifWarrantyIndifWarrantyIndifStandbys 6.5WRegulations / CertificationsHDMIWeits in the Box?IndifPower Consumption (Typical)S forwarrantRegulations / CertificationsIndifWeits in the Box?Erture Formanication (Indi	SPDIF Audio Output	1 x SPDIF (Optical, Black)
Anaga Audio Output (L + R)1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)Mechanical FeaturesChassis ColorsBlack HousingStand TypeMatted-Finished MetalWall MountableYesWall Mount Screw Size (mm)M6 x 9mmStand DetachableCapableBezel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Binn DesignUttra SlimVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)DimensionsVesWith Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Without Stand (Inches, W x H x D)2.0 lbsRegight with Stand (Ibs)2.0 lbsGross Weight without Stand (Ibs)2.0 lbsPowerStand Screw Size (Iss)Power Range (V, A, Hz)100 - 240VAC, 60/S0Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/S0Hz, 24 (Max.)Power Consumption (Tipcial)73WStandbya 50WStandbya 50WRegulations / CertificationsHDMIWarantyIfoWUmarity FC, ISTA 3A, ISTA 6A, HDMICertificationsNor YearPower CableAC Power Cable x 1AccessoriesSipaly,Stand (Left & Fight), Ligser Guide, Waranty Card,	USB	1 x USB 2.0
Mechanical Features       Chasis Colors     Black Housing       Stand Type     Matted-Finished Metal       Wall Mountable     Yes       Wall Mountable     Yes       Wall Mountable     Yes       Stand Detachable     Capable       Bezel Width     Top, Lett and Right: 0.48"; Bottom: 0.85"       Slin Design     Ultra Slim       VESA Mount Pattern (mm)     400mm x 200mm       Base Detachable     Yes       Stand Strew Size & Quantity (mm)     M4 x 14mm (4pcs)       Dimensions	Composite Video	1 x Composite (Video and Audio ports share with Component)
Chasis ColorsBlack HousingStand TypeMatted-Finished MetalWall MountableYesWall Mount Screw Size (mm)M6 x 9mmStand DetachableCopableBezel WidthTop, Left and Right: 0.48" ; Bottom: 0.85"Sim DesignUltra SlimVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)DimensionsVith Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)20.10sNet Weight with Stand (lbs)2.0 lbsPowerPower Sange (v, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Sange (v, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Colspan="2">Consumption (Typical)370WCarton Soc Subject (Colspan="2">Carton Soc Subject	Analog Audio Output (L + R)	1 (2 x RCA terminals (White, Red)) via Mini Line Out jack (Cable not included)
Stand TypeMatted-Finished MetalWall Mount Screw Size (nm)Ks 9mmStand DetachableCapableBazel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Bin DesignUltra SilmVESA Mount Pattern (nm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (nm)Wk 14mm (4pcs)DimensionsVitra SilmVith Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"With Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)20.9 lbsGross Weight with Stand (lbs)22.0 lbsNet Weight without Stand (lbs)23.0 lbsPowerSo 2 lbsPower Sange (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Consumption (Typical)73WRagulations / Certificationss 0.5WRegulations / Certificationss 0.5WRegulations / CertificationsS (ETLus, FCC, ISTA 3A, ISTA 6A, HDMIWarrantyVeraPower CableA Power Cable x 1AccessoriesDisplay,Stand (Left & Right),Uer Guide,Warranty Card,Siznd (Left & Right),	Mechanical Features	
Wall MountableYesWall Mount Screw Size (mm)M6 x 9mmStand DetachableCapableBezel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Bezel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Silm DesignUltra SilmVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)Dimensions43.4" x 27.5" x 9.5"Without Stand (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Weight43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Weight With Stand (lbs)22.0 lbsStand Screw Size (MA)20.9 lbsGross Weight (lbs)3.5 l lbsPower52 lbsPower Consumption (Typical)73WMaximum< 160W	Chassis Colors	Black Housing
Wall Mount Screw Size (mm)Mé x 9mmStand DetachableCapableBezel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Slim DesignUltra SlimVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)43.4" x 27.5" x 9.5"With Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"WeightVesWeightVesWeight with Stand (Ibs)22.0 lbsNet Weight without Stand (Ibs)22.0 lbsNet Weight without Stand (Ibs)20.9 lbsGross Weight (Ibs)35.2 lbsPowerStandbyPower Consumption (Typical)73WMaximum< 160W	Stand Type	Matted-Finished Metal
Stand DetachableCapableBezel WidthTop, Left and Right: 0.48"; Bottom: 0.85"Sim DesignUltra SimVESA Mount Pattern (mm)400mm x 200mnBase DetachableYesStand Scree Size & Quantity (mm)M4 x 14mm (4pcs)DimensionsWith Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)22.0 lbsNet Weight with Stand (lbs)22.0 lbsNet Weight with Stand (lbs)20.9 lbsGross Weight (lbs)35.2 lbsPowerSize JosPower Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5 WRegulations / CertificationsETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsCertureWirrantyLinche K ight), User Guide, Warranty Card,	Wall Mountable	Yes
Bezel Width     Top, Left and Right: 0.48"; Bottom: 0.85"       Slim Design     Ultra Slim       Slim Design     400mm x 200mm       Base Detachable     Yes       Stand Screw Size & Quantity (mm)     4x 14mm (4pcs)       Dimensions     Vers       With Stand (inches, W x H x D)     43.4" x 25.5" x 9.5"       Without Stand (inches, W x H x D)     43.4" x 25.2" x 3.2"       Carton Box Dimension (inches, W x H x D)     43.4" x 25.2" x 3.2"       Vergint     Vergint       Net Weight with Stand (lbs)     2.0 lbs       Gross Weight (lbs)     3.5.2 lbs       Power     Standby       Power Consumption (Typical)     3.4000       Maximum     100 - 240VAC, 60/50Hz, 2A (Max.)       Power Consumption (Typical)     3.5000       Standby     s 0.5000       Regulations / Certifications     100 - 240VAC, 60/50Hz, 2A (Max.)       Regulations / Certifications     s 0.5000       Regulations / Certifications     100 - 240VAC, 60/50Hz, 2A (Max.)       Regulations / Certifications     100 - 240VAC, 60/50Hz, 2A (Max.)       Regulations / Certifications     100 - 240VAC, 60/50Hz, 2A (Max.)	Wall Mount Screw Size (mm)	M6 x 9mm
Slim DesignUtra SlimVESA Mount Pattern (mm)400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)DimensionsWith Stand (inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"VeightWeightWeightVeight with Stand (lbs)2.0 lbsGross Weight (lbs)3.2 lbsPowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Colspan="2">Power Colspan="2">Cartificationsa 100 - 240VAC, 60/50Hz, 24 (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 24 (Max.)Power Colspan= 2Power Colspan= 2Regulations / Certificationsa 100 - 240VAC, 60/50Hz, 24 (Max.)Power Colspan= 2Regulations / Certifications	Stand Detachable	Capable
Version400mm x 200mmBase DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)Dimensions43.4" x 27.5" x 9.5"With Stand (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"WeightVersion (Inches, W x H x D)Weight with Stand (lbs)2.0 lbsStand Screw Size & Quantity (mb)20.9 lbsPower Meight without Stand (lbs)2.0.9 lbsPower Renge (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearWhat's in the Box?Display,Power CableA CPower Cable x 1AccessoriesDisplay,Stand (Left & Right), User Guide, Warranty Card,	Bezel Width	Top, Left and Right: 0.48" ; Bottom: 0.85"
Base DetachableYesStand Screw Size & Quantity (mm)M4 x 14mm (4pcs)Dimensions43.4" x 27.5" x 9.5"With Stand (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)X7" x 30.1" x 6.9"WeightVeightWeight with Stand (lbs)22.0 lbsNet Weight with Stand (lbs)20.9 lbsGross Weight (lbs)35.2 lbsPowerVewer Ange (V, A, Hz)Power Range (V, A, Hz)100 · 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandbyso.5WRegulations / CertificationsHDMIVarrantyLimited Parts and LaborVarrantyOne YearPower CableA CPower Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Slim Design	Ultra Slim
Stand Screw Size & Quantity (mm)M4 x 14mm (4pcs)DimensionsWith Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)47.7" x 30.1" x 6.9"WeightVeightNet Weight with Stand (Ibs)22.0 lbsGross Weight (Ibs)20.9 lbsGross Weight (Ibs)25.2 lbsPowerVerePower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / Certifications6150WVerarity(ETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsDone YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	VESA Mount Pattern (mm)	400mm x 200mm
DimensionsWith Stand (Inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)47.7" x 30.1" x 6.9"WeightVeightNet Weight with Stand (Ibs)22.0 lbsSores Weight (Ibs)25.2 lbsPowerStand (Ibs)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsRegulationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Base Detachable	Yes
With Stand (inches, W x H x D)43.4" x 27.5" x 9.5"Without Stand (inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (inches, W x H x D)7.7" x 30.1" x 6.9"Weight2.0. IbsNet Weight with Stand (lbs)2.0. IbsSoress Weight (lbs)35.2 lbsPowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum< 160W	Stand Screw Size & Quantity (mm)	M4 x 14mm (4pcs)
Without Stand (Inches, W x H x D)43.4" x 25.2" x 3.2"Carton Box Dimension (Inches, W x H x D)>7.7" x 30.1" x 6.9"WeightX7.7" x 30.1" x 6.9"Weight with Stand (Ibs)22.0 lbsRet Weight without Stand (Ibs)20.9 lbsGross Weight (Ibs)35.2 lbsPower100 - 240VAC, 60/50Hz, 2A (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / Certifications6TLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsMIWarrantyLimited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Dimensions	
Carton Box Dimension (inches, W x H x D¥7.7" x 30.1" x 6.9"WeightXXXXXXXXXXNet Weight with Stand (lbs)22.0 lbs20.9	With Stand (inches, W x H x D)	43.4" × 27.5" × 9.5"
Weight       Net Weight with Stand (lbs)     22.0 lbs       Net Weight without Stand (lbs)     20.9 lbs       Gross Weight (lbs)     35.2 lbs       Power        Power Range (V, A, Hz)     100 - 240VAC, 60/50Hz, 2A (Max.)       Power Consumption (Typical)     73W       Maximum     ≤ 160W       Standby     ≤ 0.5W       Regulations / Certifications     ≤ 0.5W       Regulations     CETLus, FCC, ISTA 3A, ISTA 6A, HDMI       Certifications     HDMI       Warranty        Limited Parts and Labor     One Year       What's in the Box?     Power Cable x 1       Accessories     Display, Stand (Left & Right), User Guide, Warranty Card,	Without Stand (Inches, W x H x D)	43.4" x 25.2" x 3.2"
Net Weight with Stand (lbs)22.0 lbsNet Weight without Stand (lbs)20.9 lbsGross Weight (lbs)35.2 lbsPowerPowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMIVarrantyULimited Parts and LaborOne YearWhat's in the Box?AC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Carton Box Dimension (inches, W x H x	(D)47.7" x 30.1" x 6.9"
Net Weight with Stand (lbs)22.0 lbsNet Weight without Stand (lbs)20.9 lbsGross Weight (lbs)35.2 lbsPowerPowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMIVarrantyULimited Parts and LaborOne YearWhat's in the Box?AC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Weight	
Net Weight without Stand (lbs)20.9 lbsGross Weight (lbs)35.2 lbsPowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		22.0 lbs
Gross Weight (lbs)35.2 lbsPower100 - 240VAC, 60/50Hz, 2A (Max.)Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyUinited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		20.9 lbs
PowerPower Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborUhat's in the Box?One YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	Gross Weight (lbs)	35.2 lbs
Power Range (V, A, Hz)100 - 240VAC, 60/50Hz, 2A (Max.)Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsRegulationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	-	
Power Consumption (Typical)73WMaximum≤ 160WStandby≤ 0.5WRegulations / CertificationsETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyUarrantyLimited Parts and LaborOne YearPower CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		100 - 240VAC 60/50Hz 2A (Max )
Maximum≤ 160WStandby≤ 0.5WRegulations / CertificationsRegulationsCETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearWhat's in the Box?Power CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		
Standby ≤ 0.5W   Regulations / Certifications ETLus, FCC, ISTA 3A, ISTA 6A, HDMI   Certifications HDMI   Warranty Uinited Parts and Labor   One Year One Year   What's in the Box? Power Cable   Power Cable AC Power Cable x 1   Accessories Display, Stand (Left & Right), User Guide, Warranty Card,		
Regulations / CertificationsRegulationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyLimited Parts and LaborOne YearWhat's in the Box?Power CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		
RegulationscETLus, FCC, ISTA 3A, ISTA 6A, HDMICertificationsHDMIWarrantyUnited Parts and LaborUmited Parts and LaborOne YearWhat's in the Box?AC Power Cable x 1Power CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,	-	
CertificationsHDMIWarrantyLimited Parts and LaborOne YearWhat's in the Box?Power CableAC Power Cable x 1AccessoriesDisplay, Stand (Left & Right), User Guide, Warranty Card,		
WarrantyLimited Parts and LaborOne YearWhat's in the Box?Power CableAC Power Cable x 1AccessoriesDisplay,Stand (Left & Right), User Guide, Warranty Card,		
Limited Parts and Labor   One Year     What's in the Box?   AC Power Cable x 1     Power Cable   AC Power Cable x 1     Accessories   Display,     Stand (Left & Right),   User Guide,     Warranty Card,   Warranty Card,		
What's in the Box?     Power Cable   AC Power Cable x 1     Accessories   Display,     Stand (Left & Right),   User Guide,     Warranty Card,   Warranty Card,		
Power Cable   AC Power Cable x 1     Accessories   Display,     Stand (Left & Right),   User Guide,     Warranty Card,   Warranty Card,		Une rear
Accessories Display, Stand (Left & Right), User Guide, Warranty Card,		
Stand (Left & Right), User Guide, Warranty Card,		AC Power Cable x 1
User Guide, Warranty Card,	Accessories	
Warranty Card,		-
Screws for Neck,		
		Screws for Neck,



SCEPTRE	
	Screwdriver,
	Remote Control
Remote Control Model No	<a< td=""></a<>
	href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-142021
	270009C-product742category19category69.html">142021270009C





### LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.





## **UHD Upscaling**

Breathing new life into the colors of older movies and shows, UHD Upscaling upgrades SD, HD, FHD resolution nearly to the level of the masterful 4K picture quality the UHD display has to offer.

# **Halo Stand Design**

Sleek and slender, Sceptre's Halo Stand Design is remarkably light in weight while still providing a durable metallic frame that balances the weight of the TV more evenly and efficiently than previous designs.



#### **Multiple Ports**

4 HDMI ports deliver sharply crafted images during fast-paced action scenes. Component & Composite ports provide analog video. Audio In, a headphone jack, & optical out enhance audio.



**HDMI 2.0** 

<span style="font-family:open sans,sans-serif; font-size:14px">Connect all your favorite devices- game consoles, blu-ray devices, laptops. HDMI 2.0 ensures you get the best picture and audio quality from your 4K display.



## HDCP 2.2

HDCP 2.2 ensures that all the 4K content that is transferred from a source (Blu-Ray player, DVD player, etc.) to the display (the TV) is secured with copyright protection.





# **USB** Port

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



**Audio Return Channel (ARC)** 

a single HDMI connection to send

Audio Return Channel, or ARC, uses

audio from a TV to the SoundBar or

AV Receiver. Using one HDMI cable,

video is send to the TV with an HDMI cable, and that same HDMI cable sends audio from the TV back down

the same cable.



# CEC

The CEC (Consumer Electronics Control) feature effortlessly allows users to control HDMI connected devices with only one remote.



### **VESA Wall Mountable**

The VESA wall mount provides the ideal position to view your TV and eliminates cable clutter, contributing a stylishly modern addition to your decor.



### **Customer Service**

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



### **30+ Years of Experience**

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.