

X325BV-FSR 32" LED TV



Specification

Display	
Active Screen Size	31.5" Diagonal Viewable
Panel Type	IPS (In-Plane Switching)
Native Resolution	1920 x 1080
Refresh Rate	MEMC 120
Aspect Ratio	16:9
Display Colors	16.7M (8-bits)
Response Time	8ms (G-to-G)
Pixel Pitch	0.36375mm (H) x 0.36375mm (V)
Dynamic Contrast Ratio	1,000,000:1
Color Gamut	sRGB: 100% DCI-P3: 82%
Contrast Ratio	3,000:1
Brightness (Typ.)	250 cd/m²
Viewing Angle	178° (Horizontal) / 178° (Vertical)
Backlight Life	50,000+ Hours
Surface Treatment	Antiglare (Haze 1%)
Features	

On Screen Display Control (OSD)	Picture, Sound, Channel, Setup
Color Temperature	Warm, Normal, Cool, Standards
Support MHL	Yes
Adjustable Picture Control*	Brightness, Contrast, Backlight, Color, Tint, Sharp
Picture Presets	Normal, Wide, Cinema, Zoom
Built-in Tuner	ATSC / NTSC / Clear QAM
OSD Supported Languages	English (Default), Spanish, French, Chinese
Weak Signal Enhancement	Yes
Comb Filter	3D
De-interlace Technology	3D
Auto Dynamic Contrast Mode	Yes
Noise Reduction	Yes
MPEG Noise Reduction	Yes
Surround Sound Mode	Yes
Sound Equalizer Settings	Yes
Auto Volume Level Control	Yes
Wall Mountable	Yes
Energy Guide	Yes

Audio Features

Speakers	2 ×10W/6Ω
----------	-----------

Video Features

White Balance	Available
---------------	-----------

Inputs & Outputs

HDMI (# of Ports & Version)	3 × HDMI (only HDMI1 with MHL function)
Supported HDMI Signals	Up to 1920 x 1080@ 60Hz (Native & Max)
Cable / Antenna Input	1 × IEC-Connector 75Ω
3.5mm Auxiliary Input Jack	1 × PC Audio in terminal (black)
Supported HDTV Signals	1080p,1080i, 720p, 480p, 480i
SPDIF Audio Output	1 × SPDIF (Optical, Black)
Component (YPbPr) Input	1 × Component
3.5mm Headphone Jack (Output)	1 × Earphone terminal (black)
Supported VGA Signals	1 × D-SUB terminal (Blue, 15 pin)
USB	1 × USB 2.0
Composite Video	1 × Composite (Video and Audio share with YPbPr)

Mechanical Features


Stand Detachable	Yes
VESA Mount Pattern (mm)	200mm x 200mm
VESA Mount Screw Size (mm)	M6 x 10mm
Stand Screw Size & Quantity (mm)	ST4 x 16mm (4pcs)

Dimensions

With Stand (inches, W x H x D)	28.78" x 18.34" x 7.94"
Without Stand (Inches, W x H x D)	28.78" x 16.96" x 3.56"
Carton Box Dimension (inches, W x H x D)	32.17" x 20.94" x 5.51"

Weight	
Net Weight with Stand (lbs)	9.20 lbs
Net Weight without Stand (lbs)	9.02 lbs
Gross Weight (lbs)	12.88 lbs
Power	
Power Range (V, A, Hz)	100 - 240V~, 50/60Hz, 3.0A (Max.)
Power Consumption (Typical)	27 W
Maximum	48 W
Standby	≤0.5 W
Regulations / Certifications	
Regulations	cTUVus, FCC, Energy Star 7.0, ISTA 6A
Certifications	HDMI, MHL
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Power Adapter x 1
Accessories	Display x 1, Stand x 1 (2 legs), Screw Driver x 1, Stand Screws x 4, Remote Control x 1, User Guide x 1
Remote Control Model No	8142026670003C

Key Features



LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.



VGA

With the ability to connect your computer, laptop, monitor, or TV to all your favorite variety of input options, VGA inputs deliver superb analog video.



USB Port

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



Energy Star V7.0

By meeting EPA and DOE standards, Sceptre's ENERGY STAR-qualified products prevent greenhouse gas emissions and provide energy savings for customers.



Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.

Key Features



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.