

E258B-1658A 25" LED Monitor



Specification

Display	
Display	
Active Screen Size	24.5" Diagonal Viewable
Panel Type	TN (Twisted Nematic)
Native Resolution	1920 x 1080
Refresh Rate	Up to 165Hz Refresh Rate
Aspect Ratio	16:9
Response Time	1 ms (G-to-G)
Pixel Pitch	0.2832mm (H) x 0.2802mm (V)
Dynamic Contrast Ratio	5,000,000: 1
Color Gamut	sRGB:94% DCI-P3:76%□
Color Depth	16.7M (RGB 6-bit Hi-FRC)
Contrast Ratio	3,000: 1
Brightness (Typ.)	300 cd/m ²
Viewing Angle	Vertical: 170° / Horizontal: 178°
Backlight Life	30,000+ Hours
Anti-Flicker	Yes
Surface Treatment	Antiglare (Haze 25%), Hard coating (3H)

On Screen Display Control (OSD) On Screen	SCEPTRE®	
Color Temperature Warm, Normal (Default), Cool, User Picture Presets Standard, User, Movie, Eco, FPS, RTS Game Presets FPS and RTS SOD Supported Languages English (Default), French, Spanish, Chinese Type of Sync AMD FreeSync™ Compatible Blue Light Shift Available Overdrive Yes Auto Dynamic Contrast Mode Available Gamma Adjustable Auto Dynamic Contrast Mode Available Auto Dynamic Contrast Mode 2 x HDMI (2.0 & 1.4) Supported HDMI Signals	Features	
Picture Presets Standard, User, Movie, Eco, FPS, RTS Game Presets FPS and RTS DSD Supported Languages English (Default), French, Spanish , Chinese Type of Sync AMD FreeSync™ Compatible Blue Light Shift Available Overdrive Yes Auto Dynamic Contrast Mode Available Audio Eatures Speakers 2 x 2W/80 Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Machanical Features Tilt Backward: 1.5° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Pattern (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (Inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 20.54	On Screen Display Control (OSD)	Quick Start, Picture, Color, System
Game Presets FPS and RTS OSD Supported Languages English (Default), French, Spanish , Chinese Type of Sync AMD FreeSync™ Compatible Bilue Light Shift Available Overdrive Yes Auto Dynamic Contrast Mode Available Gamma Adjustable Audio Foatures Speakers Speakers 2 x 2W/8Ω Inputs & Amp; Outputs Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Tilt Backward: 15* Forward: 5* Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size & Quantity (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 7mm With Stand (lines, W x H x D) 21.96* x 15.94* x 7.35** With Stand (lines, W x H x D) 21.96*	Color Temperature	Warm, Normal (Default), Cool, User
SDS Supported Languages Type of Sync AMD FreeSync™ Compatible Blue Lipht Shift Available Overdrive Yes Auto Dynamic Contrast Mode Adjustable Auto Dynamic Contrast Mode Adjustable Auto Pynamic Contrast Mode Adjustable Auto Pynamic Contrast Mode Audio Features Speakers 2 x 2W/8Ω Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimonsions With Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (Inches, W x H x D) Net Weight with Stand (Ibs) 7.50 lbs Gross Weight without Stand (Ibs) 7.50 lbs Gross Weight without Stand (Ibs) 7.50 lbs Ret Weight without Stand (Ibs) 7.50 lbs Ret Weight without Stand (Ibs) 7.50 lbs Gross Weight (Ibs) 7.50 lbs Power Power Power Range (V, A, Hz) 100 − 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) Sleep 4.0.5W Sleep 5.0.5W Sleep 5	Picture Presets	Standard, User, Movie, Eco, FPS, RTS
Type of Sync AMD FreeSync™ Compatible Blue Light Shift Available Overdrive Yes Available Gamma Adjustable Auto Dynamic Contrast Mode Available Gamma Adjustable Audio Features Speakers 2 x 2W/80 Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.50 lbs Forss Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Game Presets	FPS and RTS
Blue Light Shift Available Overdrive Yes Auto Dynamic Contrast Mode Adjustable Adjustable Adjustable Adjustable Adjustable Adjustable Aldio Features Speakers 2 x 2W/8Q Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Forew Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (Ibs) 7.50 lbs Gross Weight (Ibs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.14 (Max.) Power Consumption (Typical) 27W Maximum 30W Slandby <0.5W Sleep <0.5W Cepture Available A	OSD Supported Languages	English (Default), French, Spanish , Chinese
Overdrive Yes Auto Dynamic Contrast Mode Available Audio Features Very 2 x 2 W/8Ω Inputs & Amp; Outputs Very 2 x 1080 @ 165Hz HDMI (# of Ports & Version) 2 x 1080 @ 165Hz Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (Inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Weight with Stand (lbs) 7.50 lbs <t< td=""><td>Type of Sync</td><td>AMD FreeSync™ Compatible</td></t<>	Type of Sync	AMD FreeSync™ Compatible
Auto Dynamic Contrast Mode Gamma Adjustable Audio Features Speakers 2 x 2W/8Ω Inputs & Amp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mochanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) Y5mm x 75mm VESA Mount Pattern (mm) Neck Screw Size & Quantity (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) Net Weight Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) Power Consumption (Typical) Auton Auton Screw Size (Note of the Consumer of	Blue Light Shift	Available
Adjustable Audio Features Speakers 2 x 2W/8Ω Inputs & Semp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96° x 15.94" x 7.35" Without Stand (inches, W x H x D) 22.96° x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.4.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, H2) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby < 0.5W Sleep < 0.5W Off < 0.5W Regulations / Certifications	Overdrive	Yes
Audio Features Speakers 2 x 2W/8Ω Inputs & Samp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 ⊕ 165Hz Df (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 ⊕ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Pattern (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 22.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby < 0.5W Regulations / Certifications	Auto Dynamic Contrast Mode	Available
Speakers 2 x 2W/8Ω Inputs & Samp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Weight Net Weight with Stand (lbs) 7.50 lbs Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 7.55 lbs Power 10.58 lbs Power 27W Maximum 30W	Gamma	Adjustable
Inputs & Samp; Outputs HDMI (# of Ports & Version) 2 x HDMI (2.0 & 1.4) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (libs) 7.50 lbs Net Weight with Stand (lbs) 7.50 lbs Fower Range (V, A, Hz) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consu	Audio Features	
HDMI (# of Ports & Version) Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Neck Screw Size & Quantity (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (ibs) 7.50 lbs Net Weight without Stand (ibs) 7.50 lbs Net Weight (ibs) 10.58 lbs Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum 30W Standby <0.5W Regulations / Certifications	Speakers	2 x 2W/8Ω
Supported HDMI Signals Up to 1920 x 1080 @ 165Hz DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Weight Weight 5.0 lbs Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W <th< td=""><td>Inputs & Outputs</td><td></td></th<>	Inputs & Outputs	
DP (# of Ports & Version) 1 x (1.2) Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 12.84" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	HDMI (# of Ports & Version)	2 x HDMI (2.0 & 1.4)
Supported DP Signals Up to 1920 x 1080 @ 165Hz Mechanical Features Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 21.96" x 12.84" x 1.82" Weight Weight Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	Supported HDMI Signals	Up to 1920 x 1080 @ 165Hz
Mechanical Features Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight With Stand (lbs) 7.50 lbs Net Weight with Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	DP (# of Ports & Version)	1 x (1.2)
Tilt Backward: 15° Forward: 5° Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Regulations / Certifications	Supported DP Signals	Up to 1920 x 1080 @ 165Hz
Neck / Stand Detachable Yes VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	Mechanical Features	
VESA Mount Pattern (mm) 75mm x 75mm VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Weight with Stand (lbs) Net Weight without Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	Tilt	Backward: 15° Forward: 5°
VESA Mount Screw Size (mm) M4 x 7mm Neck Screw Size & Quantity (mm) M3 x 10mm Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Weight with Stand (lbs) Net Weight without Stand (lbs) 7.50 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	Neck / Stand Detachable	Yes
Neck Screw Size & Quantity (mm) Stand Screw Size & Quantity (mm) M4 x 10mm Dimensions With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 7.05 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby Standby Off O.5W Regulations / Certifications	VESA Mount Pattern (mm)	75mm x 75mm
Stand Screw Size & Quantity (mm) Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x D) Example 12.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) Carton Box Dimension (inches, W x H x D) Carton Box Dimension (inches, W x H x D) Carton Box Dimension (inches, W x H x D) Example 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Regulations / Certifications M4 x 10mm A4 x 10mm A5 x 10.94" x 10.94" x 10.94" A6 x 10.94" x 10.94" x 10.94" A7	VESA Mount Screw Size (mm)	M4 x 7mm
With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Ret Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Neck Screw Size & Quantity (mm)	M3 x 10mm
With Stand (inches, W x H x D) 21.96" x 15.94" x 7.35" Without Stand (Inches, W x H x D) 21.96" x 12.84" x 1.82" Carton Box Dimension (inches, W x H x D) 24.13" x 18.46" x 5.11" Weight Net Weight with Stand (Ibs) 7.50 lbs Net Weight (Ibs) 7.05 lbs Gross Weight (Ibs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W	Stand Screw Size & Quantity (mm)	M4 x 10mm
Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (Ibs) Net Weight without Stand (Ibs) 7.50 Ibs Gross Weight (Ibs) 7.05 Ibs 10.58 Ibs Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum 30W Standby Standby Sleep Off <0.5W Regulations / Certifications	Dimensions	
Carton Box Dimension (inches, W x H x D)24.13" x 18.46" x 5.11" Weight Net Weight with Stand (lbs) 7.50 lbs Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	With Stand (inches, W x H x D)	21.96" x 15.94" x 7.35"
WeightNet Weight with Stand (lbs)7.50 lbsNet Weight without Stand (lbs)7.05 lbsGross Weight (lbs)10.58 lbsPowerPower Range (V, A, Hz)100 - 240 VAC, 50/60 Hz, 1.1A (Max.)Power Consumption (Typical)27WMaximum30WStandby<0.5W	Without Stand (Inches, W x H x D)	21.96" x 12.84" x 1.82"
Net Weight with Stand (lbs) Net Weight without Stand (lbs) 7.05 lbs Gross Weight (lbs) 10.58 lbs Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum 30W Standby Sleep <0.5W Sleep Off <0.5W Regulations / Certifications	Carton Box Dimension (inches, W x H	x D)24.13" x 18.46" x 5.11"
Net Weight without Stand (lbs) Gross Weight (lbs) Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum Standby Sleep Off Consumption (Standby) Sleep Augustions / Certifications 7.05 lbs 10.58 lbs 10.58 lbs 10.58 lbs 10.58 lbs 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) 27W Augustions / Certifications	Weight	
Net Weight without Stand (lbs) Gross Weight (lbs) Power Power Range (V, A, Hz) Power Consumption (Typical) Maximum Standby Sleep Off Accuracy Consumption (Standby) Sleep Off Regulations / Certifications	Net Weight with Stand (lbs)	7.50 lbs
Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Net Weight without Stand (lbs)	7.05 lbs
Power Range (V, A, Hz) 100 - 240 VAC, 50/60 Hz, 1.1A (Max.) Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Gross Weight (lbs)	10.58 lbs
Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Power	
Power Consumption (Typical) 27W Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	Power Range (V, A, Hz)	100 - 240 VAC, 50/60 Hz, 1.1A (Max.)
Maximum 30W Standby <0.5W Sleep <0.5W Off <0.5W Regulations / Certifications	-	
Sleep < 0.5W Off < 0.5W Regulations / Certifications		30W
Sleep < 0.5W Off < 0.5W Regulations / Certifications	Standby	<0.5W
Off < <0.5W Regulations / Certifications	-	<0.5W
	•	<0.5W
	Regulations / Certifications	
regulations [1 CC, CTO VU3,	Regulations	FCC, cTUVus,

WHQL (Windows 10)


Certifications

SCEPTRE®

SCEP I RE	
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Cord
Display Cable	DisplayPort Cable x 1
Accessories	Monitor Display x 1,
	Stand x 1,
	Stand Screws,
	Neck Screws,
	Screw Driver x 1
	User Manual x 1



Key Features







LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.

165Hz Refresh Rate

Pushing beyond the standard refresh rate, 165Hz gives gamers an edge in visibility as frames transition instantly, leaving behind no blurred images.

AMD FreeSync ™

With AMD FreeSync, gamers enjoy smooth video & seamless on the spot movement in fast-paced games. The graphic card and monitor refresh rates are synchronized to eliminate tearing and stuttering.







Edgeless Design

Edgeless Design completely immerses you in all the captivating action and wondrous scenery that 1080P resolution and 165Hz refresh rate have to offer.

HDMI and DisplayPort

Two HDMI ports and one DisplayPort provide up to 165Hz refresh rate, delivering a versatile advantage in all action-packed gaming sequences.

Built-in Speakers

Perfectly suited to work & gaming settings, built-in speakers deliver robust & smooth audio while saving space on your desk.



Key Features







Blue Light Shift

Blue Light Shift reduces blue light, allowing you to comfortably work, watch, or play applications without straining your eyes.

Anti-Flicker

Provides a crisper picture by preventing the backlight from flickering periodically.

FPS-RTS Game Modes

FPS and RTS are Sceptre's custom set display settings built for an enhanced gaming experience. FPS (First Person Shooter), RTS (Real-Time Strategy).







Tiltable Display

A display that tilts 15° backward and 5° forward allows you to find a sweet spot that bridges clarity and comfort.

VESA Wall Mountable

The VESA wall mount pattern gives you the freedom to select the optimum viewing position for your monitor, eliminate cable clutter, and save valuable space for your gaming and work station.

Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



Key Features



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.