

X425BV-FHD3 42' LCD TV



Specification

| Display | | |
|---------------------------------|--|--|
| Active Screen Size | 42" (42.02" Diagonal corner to corner) | |
| Native Resolution | 1920 x 1080 | |
| Contrast Ratio | 50,000 :1 (Dynamic) | |
| LCD Panel | | |
| Aspect Ratio | Wide Screen 16:9 | |
| Refresh Rate | 60 Hz | |
| Brightness | 400 cd/m2 | |
| Response Time | 6.5 ms (G-to-G) | |
| Colors | 16.7M (8-bit) | |
| Lamp Life | 50,000+ Hour | |
| Viewing Angle | 178º (Horizontal) / 178º (Vertical) | |
| Features | | |
| On Screen Display Control (OSD) | Picture, Sound, Channel, Parental, Setup, Others | |
| Built-in Tuner | ATSC / NTSC / Clear QAM | |
| OSD Supported Languages | English (Default), French, Spanish | |
| Weak Signal Enhancement | Yes | |

| SCEPTRE® | |
|---|---|
| Comb Filter | 3D |
| De-interlace Technology | 3D |
| Auto Dynamic Contrast Mode | Yes |
| Noise Reduction | Yes |
| MPEG Noise Reduction | Yes |
| Built-in Speakers | 10 watts per Channel x 2 |
| Surround Sound Mode | Yes (SRS TruSurround HD) |
| Sound Equalizer Settings | Yes (7-band) |
| Auto Volume Level Control | Yes |
| Wall Mountable | Yes |
| Swivel Angles | +/- 35 degree |
| Neck & Base Detachable | Yes |
| Energy Guide | X425BV-FHD3 |
| Outputs | |
| Analog Audio Output (L + R) | 1 (2 × RCA terminals (white, red)) |
| Headphone Output | 1 × Earphone terminal (black) |
| Inputs | |
| PC Audio In | $1 \times$ Audio In terminal (black) |
| HDTV Signal Compatibility | |
| VGA Input Support | 1920 x 1080 @ 60Hz (Native & Max) 1680 x 1050 @ 60Hz 1360 x 768 @ |
| | 60Hz br />1280 x 1024 @ 60Hz 1024x768 @ 60Hz 800x600 @ 60Hz |
| Inputs & amp; Outputs | |
| inputs damp, Outputs | |
| HDMI (# of Ports & Vorsion) | |
| HDMI (# of Ports & Version) | 3 x HDMI |
| Supported HDMI Signals | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i |
| Supported HDMI Signals Cable / Antenna Input | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Dimensions | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm M6 x 22mm |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Dimensions With Stand (inches, W x H x D) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm M6 x 22mm 40.15" x 10.24" x 27.3" |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm M6 x 22mm 40.15" x 10.24" x 27.3" 40.15" x 3.46" x 25.12" |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm M6 x 22mm 40.15" x 10.24" x 27.3" 40.15" x 3.46" x 25.12" |
| Supported HDMI Signals Cable / Antenna Input Supported HDTV Signals SPDIF Audio Output VGA (# of Ports) Component (YPbPr) Input USB Composite Video Mechanical Features VESA Mount Pattern (mm) VESA Mount Screw Size (mm) Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm × 200mm M6 × 22mm 40.15" × 10.24" × 27.3" 40.15" × 3.46" × 25.12" D/46.1" × 6.6" × 31.1" |
| Supported HDMI SignalsCable / Antenna InputSupported HDTV SignalsSPDIF Audio OutputVGA (# of Ports)Component (YPbPr) InputUSBComposite VideoMechanical FeaturesVESA Mount Pattern (mm)VESA Mount Screw Size (mm)DimensionsWith Stand (inches, W x H x D)Without Stand (Inches, W x H x D)Carton Box Dimension (inches, W x H xWeightNet Weight with Stand (Ibs) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm × 200mm M6 × 22mm 40.15" × 10.24" × 27.3" 40.15" × 3.46" × 25.12" D/46.1" × 6.6" × 31.1" |
| Supported HDMI SignalsCable / Antenna InputSupported HDTV SignalsSPDIF Audio OutputVGA (# of Ports)Component (YPbPr) InputUSBComposite VideoMechanical FeaturesVESA Mount Pattern (mm)VESA Mount Screw Size (mm)DimensionsWith Stand (inches, W x H x D)Without Stand (Inches, W x H x D)Carton Box Dimension (inches, W x H xWeightNet Weight with Stand (Ibs)Net Weight without Stand (Ibs) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm x 200mm M6 x 22mm 40.15" x 10.24" x 27.3" 40.15" x 3.46" x 25.12" D)46.1" x 6.6" x 31.1" |
| Supported HDMI SignalsCable / Antenna InputSupported HDTV SignalsSPDIF Audio OutputVGA (# of Ports)Component (YPbPr) InputUSBComposite VideoMechanical FeaturesVESA Mount Pattern (mm)VESA Mount Screw Size (mm)DimensionsWith Stand (inches, W x H x D)Without Stand (Inches, W x H x D)Carton Box Dimension (inches, W x H xWeightNet Weight with Stand (Ibs) | 1080/24p, 1080/60p, 1080i, 720p, 480p, 480i 1 × IEC-Connector 75 Ohm 1080P, 1080i, 720P, 480P, 480i 1 × SPDIF (Coaxial, Orange) 1 × D-SUB terminal (blue, 15 pin) 1 × Component (Audio input share with composite) 1 × USB 2.0 1 × Composite 400mm × 200mm M6 × 22mm 40.15" × 10.24" × 27.3" 40.15" × 3.46" × 25.12" D/46.1" × 6.6" × 31.1" |

| SCEPTRE® | |
|------------------------------|---|
| Power Range (V, A, Hz) | 110 ~ 240V, 60/50 Hz, 3.0A (Max.) |
| Power Consumption (Typical) | 110 W (Maximum) 81 W (Typical) \leq 0.5 W (Standby) |
| Regulations / Certifications | |
| Certificates | FCC, cTUVus, Energy Star V5.3, SRS TruSurround HD, ISTA 3A |
| Warranty | |
| Limited Parts and Labor | One Year |
| What's in the Box? | |
| Remote Control Model No | <9 |
| | href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-142021 |
| | 270010C-product745category19category69.html">142021270010C |





Swivel Base

The swivel base allows you to rotate your HDTV up to +/- 15 degrees so you can obtain the best view of the screen in all its brilliant clarity.



HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.



Parental Control

Limits TV and movie viewing based on movie & TV rating as you select each rating. V-chip provides parents with the ability to determine their children's viewing options based on the movie and television content rating system.



USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



Analog Audio Out

Offering superior backwards compatibility for stereo receivers, Sceptre TVs are built with a pair of analog RCA audio outputs which will enrich your audio experience without the necessity of purchasing new digital audio equipment.



Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.





30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.