

X460BV-F120 46" LCD HDTV



Specification

Display		
Active Screen Size	46" (46" Diagonal corner to corner)	
Native Resolution	1920 x 1080	
Dynamic Contrast Ratio	20,000:1	
Contrast Ratio	4,000 : 1	
LCD Panel		
Aspect Ratio	Wide Screen 16:9	
Refresh Rate	120 Hz	
Brightness	550 cd/m2	
Response Time	6 ms (G-to-G)	
Colors	16.7M	
Lamp Life	50,000+ Hour	
Viewing Angle	178º (Horizontal) / 178º (Vertical)	
Features		
On Screen Display Control (OSD)	Video, Audio, TV, Setup, Parental	
Built-in Tuner	ATSC / NTSC / Clear QAM	
OSD Supported Languages	English (Default), French, Spanish	

Weak Signal Enhancement Yes Comb Filter 3D De-interiace Technology 3D Auto Dynamic Contrast Mode Yes Noise Reduction Yes Built-in Speakers 1D walts per channel x 2 Auto Volume Level Control Yes Wall Mountable Yes Swivel Angles 4-7 30 degree Neck & Base Detachable Yes Swivel Angles 4-7 30 degree Neck & Base Detachable Yes Energy Guide A6608V-F120 Outputs 1 x Earphone terminal (black) Inputs 1 x Audio in terminal (black) Inputs & Ampro Output 1 x Earphone terminal (black) Inputs & Ampro Outputs 1 x Audio in terminal (black) Inputs & Ampro Outputs 1 x Audio in terminal (black) Inputs & Ampro Outputs 1 x Earphone terminal (black) Inputs & Ampro Outputs 1 x Earphone terminal (black) Supported HDM Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Supported HDM Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Supported HDM Signals 1080/24p, 1	SCEPTRE®	
De-interlace Technology	Weak Signal Enhancement	Yes
Auto Dynamic Contrast Mode Noise Reduction Yes MPEG Noise Reduction Yes MID Mountable Yes Swivel Angles Auto Volume Level Control Yes Swivel Angles Aveck & Base Detachable Energy Guide Aveck & Base Detachable Yes Energy Guide Aveck & Base Detachable Yes Energy Guide Aveck & Base Detachable Inputs PC Audio In Inputs In	Comb Filter	3D
Noise Reduction Yes MPEG Noise Reduction Yes Built-in Speakers 10 watts per channel x 2 Auto Volume Level Control Yes Wall Mountable Yes Swivel Angles 4/- 30 degree Neck & Base Detachable Yes Energy Guide Xe608V-F120 Outputs Headphone Output 1 x Earphone terminal (black) Inputs PC Audio In 1 x Audio In terminal (black) Inputs & Audio Interminal (black) Inputs & Audio Interminal (black) </td <td>De-interlace Technology</td> <td>3D</td>	De-interlace Technology	3D
MPEG Noise Reduction Yes Built-in Speakers 10 watts per channel x 2 Auto Volume Level Control Yes Wall Mountable Yes Swivel Angles +/- 30 degree Neck & Base Detachable Yes Energy Guide X460BV-F120 Outputs Headphone Output 1 x Earphone terminal (black) Inputs 8amp; Outputs PC Audio In 1 x Audio In terminal (black) Inputs 8amp; Outputs HDMI (# of Ports & Version) 4 x HDMI Supported HDMI Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Cable / Antenna Input 1 x IEC-Connector 75 Ohm Supported HDTV Signals 1080/24p, 1080/720p, 480p, 480i SPDIF Audio Output 1 x SPDIF (Coaxial, Orange) VGA (# of Ports) 1 x D-SUB sterminal (blue, 15 pin) Component (YPbPr) Input 2 x Component USB 1 x USB 2.0 Composite Video 1 x Composite HDTV Signal Compatibility	Auto Dynamic Contrast Mode	Yes
Built-in Speakers	Noise Reduction	Yes
Auto Volume Level Control Yes Wall Mountable Yes Swivel Angles +/- 30 degree Neck & Base Detachable Yes Energy Guide X460BV-F120 Outputs Headphone Output 1 x Earphone terminal (black) Inputs 8 PC Audio In	MPEG Noise Reduction	Yes
Wall Mountable Yes Swivel Angles +/- 30 degree Neck & Base Detachable Yes Energy Guide X460BV-F120 Outputs Headphone Output 1 x Earphone terminal (black) Inputs PC Audio In 1 x Audio In terminal (black) Inputs & Amp; Outputs HDMI (# of Ports & Version) 4 x HDMI Supported HDMI Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Cable / Antenna Input 1 x IEC-Connector 75 Ohm Supported HDTV Signals 1080P, 1080i, 720P, 480P, 480i SPDIF Audio Output 1 x SPDIF (Coaxial, Orange) VGA (# of Ports) 1 x D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 x Component USB 1 x USB 2.0 Composite Video 1 x Composite HDTV Signal Compatibility VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) 60Hz 60Hz 7 > 12024 x 768 @ 60Hz 60Hz 60Hz 7 > 1024 x 768 @ 60Hz 7 > 1024 x 768 @ 60Hz 7 > 1024 x 768 @ 60Hz 7 > 1024 x 768 @ 60Hz 8 60Hz 8 60Hz <br< td=""><td>Built-in Speakers</td><td>10 watts per channel x 2</td></br<>	Built-in Speakers	10 watts per channel x 2
Swivel Angles +/- 30 degree Neck & Base Detachable Yes Energy Guide X460BV-F120 Outputs	Auto Volume Level Control	Yes
Neck & Base Detachable Yes	Wall Mountable	Yes
Energy Guide	Swivel Angles	+/- 30 degree
Dutputs	Neck & Base Detachable	Yes
Headphone Output	Energy Guide	X460BV-F120
Inputs	Outputs	
PC Audio In	Headphone Output	1 × Earphone terminal (black)
PC Audio In	Inputs	
Imputs & Eamp; Outputs		1 × Audio In terminal (black)
HDMI (# of Ports & Version) 4 x HDMI Supported HDMI Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Cable / Antenna Input 1 x IEC-Connector 75 Ohm Supported HDTV Signals 1080P, 1080i, 720P, 480P, 480i SPDIF Audio Output 1 x SPDIF (Coaxial, Orange) VGA (# of Ports) 1 x D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 x Component USB 1 x USB 2.0 Composite Video 1 x Composite HDTV Signal Compatibility VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) < br/> 60Hz < br/> 7 > 1280 x 1024 @ 60Hz < br/> 80 710 60 60Hz 80 710 60 60Hz 80 710 60 60Hz 80 710 60 60Hz 80 710 60 71 60 71 60 71 60 71 60 71 60 71 60 71 60 71 60 71 71 60 71 71 60 71 71 71 71 71 71 71 71 71 71 71 71 71	Inputs & amp: Outputs	
Supported HDMI Signals 1080/24p, 1080/60p, 1080i, 720p, 480p Cable / Antenna Input 1 × IEC-Connector 75 Ohm Supported HDTV Signals 1080P, 1080i, 720P, 480P, 480i SPDIF Audio Output 1 × SPDIF (Coaxial, Orange) VGA (# of Ports) 1 × D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 × Component USB 1 × USB 2.0 Composite Video 1 × Composite HDTV Signal Compatibility VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) 60Hz 60Hz 7 />1280 x 1024 @ 60Hz 9 60Hz 1024 x 768 @ 60Hz 9 60Hz 9 60Hz 60Hz 9 60Hz Mechanical Features VESA Mount Pattern (mm) 600 mm x 200mm VESA Mount Screw Size (mm) M8 x 25mm Dimensions With Stand (inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) H8.22" x 31.30" x 8.66" Weight Net Weight with Stand (lbs) 71.0 lb Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs)		4 × HDMI
Cable / Antenna Input 1 × IEC-Connector 75 Ohm Supported HDTV Signals 1080P, 1080i, 720P, 480P, 480i SPDIF Audio Output 1 × SPDIF (Coaxial, Orange) VGA (# of Ports) 1 × D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 × Component USB 1 × USB 2.0 Composite Video 1 × Composite HDTV Signal Compatibility VGA Input Support 1920 × 1080 @ 60Hz (Native & Max) < br/>60Hz < br/>1280 × 1024 @ 60Hz < br/>1280 × 1024 @ 60Hz < br/>1280 × 1024 % 60Hz 1280 × 1024 % 60Hz 1280 × 1024 % 60Hz 1280 × 1024 % 60Hz 		
Supported HDTV Signals 1080P, 1080I, 720P, 480P, 480I SPDIF Audio Output 1 x SPDIF (Coaxial, Orange) VGA (# of Ports) 1 x D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 x Component USB 1 x USB 2.0 Composite Video 1 x Composite HDTV Signal Compatibility 1920 x 1080 @ 60Hz (Native & Max) < br /> 1024 x 1050 @ 60Hz < br /> 1024 x 768 @ 60Hz < br /> 1024		
SPDIF Audio Output 1 × SPDIF (Coaxial, Orange) VGA (# of Ports) 1 × D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 × Component USB 1 × USB 2.0 Composite Video 1 × Composite HDTV Signal Compatibility 1920 x 1080 @ 60Hz (Native & Max) < br /> 1680 x 1050 @ 60Hz < br /> 1024x768 @ 60Hz < br /> 800x600 @ 60Hz Mechanical Features VESA Mount Pattern (mm) 600 mm x 200mm VESA Mount Screw Size (mm) M8 x 25mm Dimensions With Stand (Inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) 44.98" x 31.30" x 8.66" Weight Net Weight with Stand (lbs) 71.0 lb Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs) 86.3 lb Power	·	
VGA (# of Ports) 1 x D-SUB terminal (blue, 15 pin) Component (YPbPr) Input 2 x Component USB 1 x USB 2.0 Composite Video 1 x Composite HDTV Signal Compatibility VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) < br /> 1280 x 1024 @ 60Hz < br /> 1024x768 @ 60Hz < br /> 1024x768 @ 60Hz < br /> 800x600 @ 60Hz Mechanical Features VESA Mount Pattern (mm) 600 mm x 200mm VESA Mount Screw Size (mm) M8 x 25mm Dimensions With Stand (inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) 48.22" x 31.30" x 8.66" Weight Net Weight with Stand (lbs) 71.0 lb Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs) 86.3 lb Power		
Component (YPbPr) Input 2 × Component USB 1 × USB 2.0 Composite Video 1 × Composite HDTV Signal Compatibility VGA Input Support 1920 × 1080 @ 60Hz (Native & Max) < br />1680 x 1050 @ 60Hz < br />1024x768 @ 60Hz 1024x768 @ 60Hz < br />1024x768 @ 60Hz < br />1024x768 @ 60Hz 1024x768 @ 60Hz < br />1024x768 @ 60Hz 1024x768	<u> </u>	-
1 x USB 2.0		
Composite Video		
HDTV Signal Compatibility VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) < br /> 1680 x 1050 @ 60Hz < br /> 1360 x 768 @ 60Hz < br /> 1280 x 1024 @ 60Hz < br /> 1024x768 @ 60Hz < br /> 1024x768 @ 60Hz < br /> 800x600 @ 60Hz Mechanical Features VESA Mount Pattern (mm) 600 mm x 200mm VESA Mount Screw Size (mm) Dimensions With Stand (Inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (Ibs) 71.0 lb Net Weight without Stand (Ibs) 68.5 lb Gross Weight (Ibs) 86.3 lb Power		
VGA Input Support 1920 x 1080 @ 60Hz (Native & Max) < br/> 60Hz < br/> 1920 x 1080 @ 60Hz (Native & Max) < br/> 1024 x 1050 @ 60Hz < br/> 1024 x 1050 @ 60Hz < br/> 1024 x 1024 @ 60Hz < br/> 1024 x 1024 & 60Hz 1024 x 1024 x 1024 x 1024 x 1024 x 1024 x		
Mechanical Features VESA Mount Pattern (mm) 600 mm x 200mm		1020 v 1000 @ 60Hz (Nativo S. May) < hr /> 1600 v 1050 @ 60Hz < hr /> 1260 v 760 @
Weight Net Weight without Stand (lbs) Net Weight (lbs) Net Weight (lbs) Power	VGA IIIput Support	
VESA Mount Pattern (mm) VESA Mount Screw Size (mm) M8 x 25mm Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (lbs) Net Weight without Stand (lbs) Fower 71.0 lb Results Stand (lbs) Results Stand (lbs) Results Stand (lbs) Results Stand (lbs) Fower	Machaniaal Factures	00H2 01 />1200 x 1024 @ 00H2 01 />1024x708 @ 00H2 01 />800x000 @ 00H2
VESA Mount Screw Size (mm) Dimensions With Stand (inches, W x H x D) Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (lbs) Net Weight without Stand (lbs) Gross Weight (lbs) Power		
With Stand (inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (lbs) Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs) Power		
With Stand (inches, W x H x D) 44.98" x 31.35" x 10.7" Without Stand (Inches, W x H x D) 44.98" x 28.65" x 4.82" Carton Box Dimension (inches, W x H x D) 48.22" x 31.30" x 8.66" Weight Net Weight with Stand (lbs) 71.0 lb Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs) 86.3 lb		M8 x 25mm
Without Stand (Inches, W x H x D) Carton Box Dimension (inches, W x H x D) Weight Net Weight with Stand (Ibs) Net Weight without Stand (Ibs) Gross Weight (Ibs) Power 44.98" x 28.65" x 4.82" 44.98" x 28.65" x 4.82" 68.5 lb 68.5 lb 86.3 lb	Dimensions	
Carton Box Dimension (inches, W x H x D) 48.22" x 31.30" x 8.66" Weight Net Weight with Stand (lbs) 71.0 lb Net Weight without Stand (lbs) 68.5 lb Gross Weight (lbs) 86.3 lb Power		44.98" x 31.35" x 10.7"
WeightNet Weight with Stand (lbs)71.0 lbNet Weight without Stand (lbs)68.5 lbGross Weight (lbs)86.3 lbPower	Without Stand (Inches, W x H x D)	44.98" x 28.65" x 4.82"
Net Weight with Stand (lbs) Net Weight without Stand (lbs) Gross Weight (lbs) 86.3 lb Power	Carton Box Dimension (inches, W x H	1 x D)48.22" x 31.30" x 8.66"
Net Weight without Stand (lbs) Gross Weight (lbs) 86.3 lb Power	Weight	
Gross Weight (lbs) 86.3 lb Power	Net Weight with Stand (lbs)	71.0 lb
Power	Net Weight without Stand (lbs)	68.5 lb
	Gross Weight (lbs)	86.3 lb
Power Range (V, A, Hz) 110 ~ 240V,60/50Hz, 3.0A (Max.)	Power	
	Power Range (V, A, Hz)	110 ~ 240V,60/50Hz, 3.0A (Max.)
Power Consumption (Typical) <187W (Typical)	Power Consumption (Typical)	<187W (Typical)



<0.43W (Standby)

	Co.45W (Standby)
Regulations / Certifications	
Certificates	FCC, cTUVus, SRS TruVolume, ISTA 3A
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Remote Control Model No	-automates
	href="https://www.sceptre.com/Accessories/Remote-Control/TV-Remote-Control-KR001B
	001-product732category19category69.html">KR001B001



Key Features







Swivel Base

The swivel base allows you to rotate your HDTV up to +/- 15 degrees so you can obtain the best view of the screen in all its brilliant clarity.

HDMI

HDMI not only delivers superior digital video and audio, but also, connects both to the TV with only one cable.

Parental Control

Limits TV and movie viewing based on movie & TV rating as you select each rating. V-chip provides parents with the ability to determine their children's viewing options based on the movie and television content rating system.



USB

Let's you view your pictures as a slideshow or listen to your favorite music via the USB port. Just insert your flash drive into the USB port for the ultimate entertainment.



Analog Audio Out

Offering superior backwards compatibility for stereo receivers, Sceptre TVs are built with a pair of analog RCA audio outputs which will enrich your audio experience without the necessity of purchasing new digital audio equipment.



Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



Key Features



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.