

C325W-1920RRK 32" Curved Monitor



Specification

Display

Display	
Active Screen Size	31.5" Diagonal Viewable
Panel Type	VA (Vertical Alignment)
Curvature	1800R
Native Resolution	1920 x 1080
Refresh Rate	Up to 75Hz Refresh Rate
Aspect Ratio	16:9
Response Time	8 ms
Pixel Pitch	0.36375mm (H) x 0.36375mm (V)
Dynamic Contrast Ratio	1,000,000:1
Color Gamut	sRGB:85% DCI-P3:71%
Color Depth	16.7M
Contrast Ratio	3,000:1
Brightness (Typ.)	250 cd/m ²
Viewing Angle	178° (Horizontal) / 178° (Vertical)
Backlight Type	Edge-Lit LED
Backlight Life	50,000+ Hours

Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	SCEPTRE®		
Features On Screen Display Control (OSD) Quick Start, Picture, Color, System Color Temperature Warm, Normal (Default), Cool, User Picture Presets Standard, User, Movie, Eco, FPS, RTS Game Presets FPS and RTS OSD Supported Languages English (Default), French, Spanish , Chinese Blue Light Shift Available Auto Dynamic Contrast Mode Available Auto Standby Yes Gamma Adjustable Auto Standby Yes Speakers 2 x 3W/4Q Inputs & Amp, Outputs Supported Digital Signals Supported Digital Signals 30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical) HDMI (# of Ports & Version) 1 x HDMI Supported Digital Signals Up to 1920 x 1080 @75Hz; 1080/60p, 1080/60j, 720p, 480p, 480i DP (# of Ports & Version) 1 x DisplayPort Supported VGA Signals Up to 1920 x 1080 @75Hz; Sism Auxillay Input Jack Yes Supported VGA Signals Up to 1920 x 1080 @ 60Hz Meschanical Features Yes Supported VGA Signals Up to 1920 x 1080 @ 60Hz <td>Anti-Flicker</td> <td>Yes</td>	Anti-Flicker	Yes	
On Screen Display Control (OSD)Quick Start, Picture, Color, SystemColor TemperatureWarm, Normal (Default). Cool, UserPicture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish, ChineseBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGammaAdjustableAuto FoaturesZ XW/4QInputs & Amp? OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x DisplayPortSupported DrightalsUp to 1920 x 1080 @75Hz; 1080/60i, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported CA SignalsUp to 1920 x 1080 @75HzSupported CA SignalsUp to	Surface Treatment	Antiglare	
Color TemperatureWarm, Normal (Default), Cool, UserPicture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish, ChineseBilu Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGammaAdjustableAuto StandbyYesSpeakers2 x 3W/4QInputs & Amp; OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x IDSIapPortSupported Drigital SignalsUp to 1920 x 1080 @75Hz; 1080/601, 720p, 480p, 480iDP (# of Ports & Version)1 x IDSIapPortSupported DP SignalsUp to 1920 x 1080 @75HzSupported DP SignalsUp to 1920 x 1080 @75HzSupported CAS SignalsUp to 1920 x 1080 @75HzSupported CAS SignalsUp to 1920 x 1080 @75HzSupported CAS SignalsUp to 1920 x 1080 @75HzNechanical FeaturesYesChasis ColorsBlackTitForward: S5xdeg,Backward: 20°Neck / Stand DetachableYesSim DesignUitra SimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (Mualtity (mm)M4 x 12mmNeck Screw Size & Quantity (mm)M4 x 12mmNeck Screw Size & Quantity (mm)28.30° x	Features		
Picture PresetsStandard, User, Movie, Eco, FPS, RTSGame PresetsFPS and RTSGame PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish, ChineseBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGarmaAdjustableAuto FeaturesZ x 3W/4QSpeakers2 x 3W/4QInputs Samp; Outputs30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)Supported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)DMI (# of Ports & Version)1 x HDMISupported Digital SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60l, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @ 75Hz;Supported DP SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesYesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesYesSignal Multi A SimnYesSim DesignUltra SimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Serew Size (mm)M 4 x 12 mmNeck Serew Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Serew Size & Quantity (mm)M4 x 12 mmNeck Stand (Inches, W x H x D)28.30" x 18.60"With Stand (Inches, W x H x D)28.30" x 18.60"	On Screen Display Control (OSD)	Quick Start, Picture, Color, System	
Game PresetsFPS and RTSOSD Supported LanguagesEnglish (Default), French, Spanish , ChineseBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesGammaAdjustableAuto StandbyYesGammaAdjustableAuto Features2 x 3W/4ΩSpeakers2 x 3W/4ΩInputs Aamp; Outputs30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)DNM (# of Ports & Version)1 x HDMISupported Digital SignalsUp to 1920 x 1080 @75Hz;Supported PD SignalsUp to 1920 x 1080 @75Hz;Supported PD SignalsUp to 1920 x 1080 @75HzSupported PD SignalsUp to 1920 x 1080 @60HzMechanical FeaturesUp to 1920 x 1080 @ 60HzNechanical FeaturesUtra SimChassis ColorsBlackTiltForward: 56dsg.Backward: 20°Neck / Stand DetachableYesSim DesignUltra SimVE5A Mount Pattern (mm)100mm (W) x 100mm (H)VE5A Mount Screw Size (mm)M4 x 12mmNeck Screw Size & Quantity (mm)Xes 8.00" </td <td>Color Temperature</td> <td>Warm, Normal (Default), Cool, User</td>	Color Temperature	Warm, Normal (Default), Cool, User	
OSD Supported LanguagesEnglish (Default), French, Spanish , ChineseBlue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGammaAdjustableAuto StandbyYesSpanaAdjustableMole DesturesYesSpeakers2 x 3W/4QInputs Aamp; OutputsYesSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported PD SignalsUp to 1920 x 1080 @75Hz3.5mm Auxillary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesForward: 5°,Backward: 20°Neck / Stand DetachableYesSilm DesignUitra SlimVESA Mount Serew Size (mm)M4 x 12 mmNeck Stand DetachableYesSilm Design & Uitra Slim (pcs)Stand screw Size & Quantity (mm)VESA Mount Serew Size & Quantity (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 12 mm (pcs)Stand Screw Size & Quantity (mm)Si.30 x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Picture Presets	Standard, User, Movie, Eco, FPS, RTS	
Blue Light ShiftAvailableAuto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGarmaAdjustableAutio FeaturesZ x 3W/QSpeakers2 x 3W/QInputs & OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported DPI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxillary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesEnsist ColorsBlackTiltTiltForward: 5°.Backward: 20°Neck / Stand DetachableYesSim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size & Quantity (mm)M4 x 12mmNeck Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsDimensionWith Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Game Presets	FPS and RTS	
Auto Dynamic Contrast ModeAvailableAuto StandbyYesEnergy GuideYesGarmaAdjustableAudio Features2 x 3W/4QInputs Bamp; OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVesChasis ColorsBlackTiltForward: S°,Backward: 20°Neck / Stand DetachableYesSim DesignUltra SlimVESA Mount Pattern (mm)100mm (H) x 100mm (H)VESA Mount Screw Size (Mami)M4 x 12mmNeck Srzew Size & Quantity (mm)M4 x 12mm (2 res)DimensionsVersion (1 pcs)Stand Screw Size & Quantity (mm)Ka 12mm (2 pcs)DimensionsVersion (1 pcs)With Stand (Inches, W x H x D)28.30° x 16.68° x 3.09°	OSD Supported Languages	English (Default), French, Spanish , Chinese	
Auto StandbyYesEnergy GuideYesGammaAdjustableAudio Features2 x 3W/4ΩInputs & Outputs2 x 3W/4ΩSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz;Somm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesUp to 1920 x 1080 @ 60HzChasis ColorsBlackTitForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mn)100mm (W) x 100mm (H)VESA Mount Screw Size (mn)M4 x 12 mmNeck Screw Size & Quantity (mn)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mn)Xes Xens(1 pcs)Stand Screw Size & Quantity (mn)Xes Xens(1 pcs)Stand Screw Size & Quantity (mn)Xes Xens(1 pcs)With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	Blue Light Shift	Available	
Energy GuideYesGammaAdjustableAudio FeaturesSpeakers2 x 3W/4QInputs & OutputsSupported Digital Signals20 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDM (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75HzSomm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Auxiliary Input JackYesVGA (# of Ports)Up to 1920 x 1080 @ 60HzMechanical FeaturesUp to 1920 x 1080 @ 60HzChasis ColorsBlackTiltForward: 5°.Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mn)00mm (W) x 100mm (H)VESA Mount Screw Size & Quantity (mn)M4 x 12 mmNeck Screw Size & Quantity (mn)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mn)48 x 19.0°With Stand (inches, W x H x D)28.30° x 16.68° x 3.09°	Auto Dynamic Contrast Mode	Available	
AdjustableAudio FeaturesSpeakers2 x 3W/4QInputs Aamp: OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxillary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVersionTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Pattern (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 18.60"Without Stand (linches, W x H x D)28.30" x 16.68" x 3.09"	Auto Standby	Yes	
Audio FeaturesSpeakers2 x 3W/4ΩInputs &: OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60i, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVersionTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (quantity (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsVersionWith Stand (Inches, W x H x D)28.30" x 10.80" x 3.09"	Energy Guide	Yes	
Speakers2 x 3W/4ΩInputs & OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)DMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size & Quantity (mm)M4 x 12mmNeck Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (Inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Gamma	Adjustable	
Inputs & OutputsSupported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°.Backward: 20°Neck / Stand DetachableYesSim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mmNeck Screw Size & Quantity (mm)Xes X00"With Stand (Inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 10.68" x 3.09"	Audio Features		
Supported Digital Signals30 - 80 kHz (Horizontal) / 60 - 75 kHz (Vertical)HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVersionTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 19.80" x 8.00"With Stand (Inches, W x H x D)28.30" x 19.68" x 3.09"	Speakers	2 x 3W/4Ω	
HDMI (# of Ports & Version)1 x HDMISupported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesVesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	Inputs & Outputs		
Supported HDMI SignalsUp to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480iDP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (umm)M4 x 12 mmNeck Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	Supported Digital Signals	30 – 80 kHz (Horizontal) / 60 – 75 kHz (Vertical)	
DP (# of Ports & Version)1 x DisplayPortSupported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsUltra Slim x 8.00"With Stand (Inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	HDMI (# of Ports & Version)	1 x HDMI	
Supported DP SignalsUp to 1920 x 1080 @75Hz3.5mm Auxiliary Input JackYesVGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size & Quantity (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)83.0" x 19.80" x 8.00"With Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Supported HDMI Signals	Up to 1920 x 1080 @75Hz; 1080/60p, 1080/60i, 720p, 480p, 480i	
Additional systemYes3.5mm Auxiliary Input JackYes3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	DP (# of Ports & Version)	1 x DisplayPort	
VGA (# of Ports)1 x VGA3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 10.68" x 3.09"	Supported DP Signals	Up to 1920 x 1080 @75Hz	
3.5mm Headphone Jack (Output)YesSupported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)84.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	3.5mm Auxiliary Input Jack	Yes	
Supported VGA SignalsUp to 1920 x 1080 @ 60HzMechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)Xes X 20mm (1 pcs)Dimensions28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	VGA (# of Ports)	1 x VGA	
Mechanical FeaturesChassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	3.5mm Headphone Jack (Output)	Yes	
Chassis ColorsBlackTiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Supported VGA Signals	Up to 1920 x 1080 @ 60Hz	
TiltForward: 5°,Backward: 20°Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Mechanical Features		
Neck / Stand DetachableYesSlim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Chassis Colors	Black	
Slim DesignUltra SlimVESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Tilt	Forward: 5°,Backward: 20°	
VESA Mount Pattern (mm)100mm (W) x 100mm (H)VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Neck / Stand Detachable	Yes	
VESA Mount Screw Size (mm)M4 x 12 mmNeck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)DimensionsWith Stand (inches, W x H x D)28.30" x 19.80" x 8.00"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	Slim Design	Ultra Slim	
Neck Screw Size & Quantity (mm)M4 x 20mm (1 pcs)Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)Dimensions28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"	VESA Mount Pattern (mm)	100mm (W) x 100mm (H)	
Stand Screw Size & Quantity (mm)M4 x 12mm (2 pcs)Dimensions28.30" x 19.80" x 8.00"With Stand (inches, W x H x D)28.30" x 16.68" x 3.09"Without Stand (Inches, W x H x D)28.30" x 16.68" x 3.09"	VESA Mount Screw Size (mm)	M4 x 12 mm	
Dimensions With Stand (inches, W x H x D) 28.30" x 19.80" x 8.00" Without Stand (Inches, W x H x D) 28.30" x 16.68" x 3.09"	Neck Screw Size & Quantity (mm)	M4 x 20mm (1 pcs)	
With Stand (inches, W x H x D) 28.30" x 19.80" x 8.00" Without Stand (Inches, W x H x D) 28.30" x 16.68" x 3.09"	Stand Screw Size & Quantity (mm)	M4 x 12mm (2 pcs)	
Without Stand (Inches, W x H x D) 28.30" x 16.68" x 3.09"	Dimensions		
	With Stand (inches, $W \times H \times D$)	28.30" x 19.80" x 8.00"	
	Without Stand (Inches, W x H x D)	28.30" x 16.68" x 3.09"	
Carton Box Dimension (inches, W x H x D)30.78" x 20.03" x 5.66"			
Weight			
Net Weight with Stand (lbs) 12.45 lbs	Net Weight with Stand (lbs)	12.45 lbs	
Net Weight without Stand (lbs) 11.57 lbs	Net Weight without Stand (lbs)	11.57 lbs	
Gross Weight (lbs) 16.68 lbs	Gross Weight (lbs)	16.68 lbs	
Power			

SCEPTRE® Power Range (V, A, Hz)	AC Adapter
	Input: 100 - 240V~ 50/60Hz, 1.0A
	Output: 12V DC, 3.33A
Power Consumption (Typical)	35.6W
Maximum	40w
Standby	≤ 0.5W
Regulations / Certifications	
Regulations	FCC, cTUVus, ISTA 3A, WHQL (Win 10)
Certifications	Energy Star V7.0, HDMI
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Adapter Cable x 1
Display Cable	HDMI Cable x 1, DisplayPort Cable x 1
Accessories	Ultra Slim Monitor; Base x 1; Neck x 1; Base Screws x 1; Neck Screws x 2;Screwdriver x 1; User Manual x 1




1800R



Curved Monitor

The curved display delivers a revolutionary visual experience with a leading 1800R screen curvature as the images appear to wrap around you for an in depth, immersive experience.



LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.



75Hz Refresh Rate

With 75Hz refresh rate, images change faster and smoother than the standard, reducing screen tearing



Fast Response Time

Fast response times reduce ghosting & blurring while transitioning pixels, always keeping the enemy & terrain precisely in focus during chaotic moments.



Multiple Ports

The DisplayPort, HDMI, and VGA ports accelerate refresh rate up to 75Hz, providing the visual edge you need to defeat the competition during all of your gaming exploits.



Built-in Speakers

With built-in speakers, the monitor delivers office level audio for conference calls and internet workshops. Similarly, enjoy engaging audio while listening to your favorite tunes.





Blue Light Shift

Blue Light Shift reduces blue light, allowing you to comfortably work, watch, or play applications without straining your eyes.



Security Lock

The monitor has a security slot, allowing you to securely fasten your monitor in place, effectively preventing theft. *Security Lock not included.



Tiltable Display

A display that tilts 15° backward and 3° forward allows you to find a sweet spot that bridges clarity and comfort.



VESA Wall Mountable

The VESA wall mount pattern gives you the freedom to select the optimum viewing position for your monitor, eliminate cable clutter, and save valuable space for your gaming and work station.



Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.



30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.