

E209W-16003RT 20" LED Monitor



Specification


Display	
Active Screen Size	19.5" Diagonal Viewable
Panel Type	TN (Twisted Nematic)
Native Resolution	1600 x 900
Refresh Rate	Up to 75Hz Refresh Rate
Aspect Ratio	16:9
Response Time	3ms (G-to-G)
Pixel Pitch	0.2712mm (H) x 0.2626 mm (V)
Dynamic Contrast Ratio	1,000,000: 1
Color Gamut	NTSC:72%
Color Depth	16.7M
Contrast Ratio	3,000: 1
Brightness (Typ.)	250 cd/m²
Viewing Angle	Vertical: 160° / Horizontal: 170°
Backlight Type	Edge-lit LED
Backlight Life	30,000+ Hours
Anti-Flicker	Yes

re, Hard Coating (3H) cart, Picture, Color, System flormal (Default), Cool, User d, User, Movie, Eco, FPS, RTS RTS (Default), French, Spanish , Chinese e Sync e e e e lole 4\(\) II, 1.3 version 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA d, D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i crd: 15° Forward: 5°
Iormal (Default), Cool, User d, User, Movie, Eco, FPS, RTS RTS (Default), French, Spanish , Chinese e Sync e e e ble II, 1.3 version 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
Iormal (Default), Cool, User d, User, Movie, Eco, FPS, RTS RTS (Default), French, Spanish , Chinese e Sync e e e ble II, 1.3 version 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
d, User, Movie, Eco, FPS, RTS RTS (Default), French, Spanish , Chinese e Sync e e c ll, 1.3 version 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
RTS (Default), French, Spanish , Chinese e Sync e e c le c ll, 1.3 version S00 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out S00 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
(Default), French, Spanish , Chinese e Sync e e c le le li, 1.3 version 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
e Sync e e le le li, 1.3 version δ00 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out δ00 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
e e cole AΩ II, 1.3 version SOO x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out SOO x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
e ole 4Ω II, 1.3 version 300 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 300 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
Die 4Ω II, 1.3 version 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 600 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
II, 1.3 version Sion x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out Sion x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
II, 1.3 version 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
II, 1.3 version 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
Mini-Jack for VGA , D-sub 15 pin Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
Mini-Jack Audio Out 500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
500 x 900 @ 75Hz; 1080/60p, 1080/60i, 720p,576p,576i,480p,480i
rd: 15° Forward: 5°
rd: 15° Forward: 5°
rd: 15° Forward: 5°
75mm
mm
mm (2pcs)
Lock
x 13.58" x 7.02"
x 10.43" x 1.32"
12.8" x 4.06"
l, D1 = 7.02", D2=10.17"
5

SCEPTRE®	
Power Consumption (Typical)	18.14W
Maximum	20.45W
Standby	<0.5W
Sleep	<0.11W
Off	<0.08W
Regulations / Certifications	
Regulations	RoHS, cTUVus, FCC
Certifications	ISTA6A, HDMI
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Power Adapter x 1
Display Cable	HDMI Cable x 1
Accessories	User Manual, Warranty Card, Neck Screws x 2, Screwdriver x 1



Key Features







LED

With sharper contrasts of light and darks, LED display delivers a vast array of rich colors, ensuring that moving images have never been so pleasing to the eyes.

75Hz Refresh Rate

With 75Hz refresh rate, images change faster and smoother than the standard, reducing screen tearing

Fast Response Time

Fast response times reduce ghosting & blurring while transitioning pixels, always keeping the enemy & terrain precisely in focus during chaotic moments.







Adaptive Sync

Adaptive Sync is a technology that closes the gap between the graphics card's and the monitor's refresh rates, eliminating image tearing and stuttering in the process.

Ports

Two HDMI and one VGA port each accelerate refresh rate up to 75Hz, providing the visual edge you need to defeat the competition during all of your gaming exploits

Built-in Speakers

Perfectly suited to work & gaming settings, built-in speakers deliver robust & smooth audio while saving space on your desk.



Key Features







Blue Light Shift

Blue Light Shift reduces blue light, allowing you to comfortably work, watch, or play applications without straining your eyes.

Anti-Flicker

Provides a crisper picture by preventing the backlight from flickering periodically.

FPS-RTS Game Modes

FPS and RTS are Sceptre's custom set display settings built for an enhanced gaming experience. FPS (First Person Shooter), RTS (Real-Time Strategy).







Security Lock

The monitor has a security slot, allowing you to securely fasten your monitor in place, effectively preventing theft. *Security Lock not included.

Tiltable Display

A display that tilts 15° backward and 5° forward allows you to find a sweet spot that bridges clarity and comfort.

VESA Wall Mountable

The VESA wall mount pattern gives you the freedom to select the optimum viewing position for your monitor, eliminate cable clutter, and save valuable space for your gaming and work station.



Key Features





Customer Service

Our customer service representatives are, and have always been, based in the USA, guaranteeing that our customers' needs are met as efficiently as possible.

30+ Years of Experience

Founded in City of Industry, CA over 30 years ago, Sceptre Inc. made a promise to create & deliver superior products for remarkably affordable prices, a rare tradition that continues today.