

## C248W-FW100TR 24" Full HD100Hz Essential Curved Office LED Monitor



## Specification

## Display

Display	
Active Screen Size	23.6" Diagonal Viewable
Panel Type	VA (Vertical Alignment)
Curvature	1500R
Native Resolution	1920 x 1080 Full HD
Refresh Rate	Up to 100Hz Refresh Rate
Aspect Ratio	16:9
Response Time	5 ms
Pixel Pitch	0.09052mm(H) x 0.27156mm (V)
Dynamic Contrast Ratio	1,000,000 : 1
Color Gamut	100% sRGB
Color Depth	16.7M
Contrast Ratio	3,000: 1
Brightness (Typ.)	250 cd/m <sup>2</sup>
Viewing Angle	Vertical: 178° / Horizontal: 178°
Backlight Type	Edge-Lit LED
Backlight Life	30,000+ Hours

SCEPTRE®		
Anti-Flicker	Yes	
Surface Treatment	Antiglare	
Features		
On Screen Display Control (OSD)	Quick Start, Picture, Color, System	
Color Temperature	Warm, Normal (Default), Cool, User	
Picture Presets	Standard, User, Movie, Eco, FPS, RTS	
Game Presets	FPS and RTS	
OSD Supported Languages	English (Default), French, Spanish , Chinese	
Type of Sync	Adaptive Sync	
Blue Light Shift	Available	
Auto Dynamic Contrast Mode	Available	
Energy Guide	Yes	
Gamma	Adjustable	
Audio Features		
Speakers	$2 \times 2W/4\Omega$	
Inputs & Outputs		
HDMI (# of Ports & Version)	2 x HDMI 2.0	
Supported HDMI Signals	Up to 1920 x 1080 @ 100Hz	
VGA (# of Ports)	1 x VGA	
Supported VGA Signals	Up to 1920 x 1080 @ 75Hz	
Audio Out	1 x 3.5mm Audio Out Jack	
Mechanical Features		
Chassis Colors	Black	
Tilt	Forward: 5° Backward: 15°	
Bezel Width	7.8mm	
Neck / Stand Detachable	Yes	
Slim Design	Ultra Slim	
VESA Mount Pattern (mm)	100mm x 100mm	
VESA Mount Screw Size (mm)	M4 x 10mm	
Neck Screw Size & Quantity (mm)	M4*10mm 2pcs	
Stand Screw Size & Quantity (mm)	N/A	
Dimensions		
With Stand (inches, $W \times H \times D$ )	21.17" x 15.92" x 7.67"	
Without Stand (Inches, $W \times H \times D$ )	21.17" x 12.65" x 2.21"	
Carton Box Dimension (inches, W x H x D)24.2" x 16.5" x 4.7"		
Weight		
Net Weight with Stand (lbs)	5.82 lbs	
Net Weight without Stand (lbs)	5.14 lb	
Gross Weight (lbs)	11.5 lbs	
Power		
Power Range (V, A, Hz)	AC Adapter	
	Input: 100 - 240V~ 50/60Hz, 1.0A	
	Output: 12V DC, 3A	
	1	

SCEPTRE®	
Power Consumption (Typical)	26W
Maximum	28W
Standby	0.29W
Regulations / Certifications	
Regulations	FCC, UL, RoHS, AER
Certifications	HDMI
Warranty	
Limited Parts and Labor	One Year
What's in the Box?	
Power Cable	AC Power Adapter x 1
Display Cable	HDMI Cable x 1
Accessories	Display x 1, Base x 1, Neck x 1, Neck Screws x 2, Sceptre Screwdriver x 1, User Manual x
	1









**Refresh Rate** 

sRGB

Curvature



Performance