

C275W-1920RND1 27" Curved Monitor



Specification

Display

Display	
Active Screen Size	27" Diagonal Viewable
Panel Type	VA (Vertical Alignment)
Curvature	1500R
Native Resolution	1920 x 1080 Full HD
Refresh Rate	Up to 100Hz Refresh Rate
Aspect Ratio	16:9
Response Time	5 ms (G to G)
Pixel Pitch	0.3108mm (H) x 0.3108 mm (V)
Dynamic Contrast Ratio	1,000,000 : 1
Color Gamut	sRGB: 98%
Color Depth	16.7M
Contrast Ratio	3,000: 1
Brightness (Typ.)	250 cd/m ²
Viewing Angle	Vertical: 178° / Horizontal: 178°
Backlight Type	Edge-Lit LED
Backlight Life	30,000+ Hours

SCEPTRE®		
Anti-Flicker	Yes	
Surface Treatment	Antiglare	
Features		
On Screen Display Control (OSD)	Quick Start, Picture, Color, System	
Color Temperature	Warm, Normal (Default), Cool, User	
Picture Presets	Standard, User, Movie, Eco, FPS, RTS	
Game Presets	FPS and RTS	
OSD Supported Languages	English (Default), French, Spanish , Chinese	
Blue Light Shift	Available	
Auto Dynamic Contrast Mode	Available	
Auto Standby	Yes	
Gamma	Adjustable	
Audio Features		
Speakers	$2 \times 2W/4\Omega$	
Inputs & Outputs		
HDMI (# of Ports & Version)	2 x HDMI 2.0	
Supported HDMI Signals	Up to 1920 x 1080 @ 100Hz, 1080p, 1080i, 720p, 480p	
VGA (# of Ports)	1 x VGA (75Hz)	
3.5mm Headphone Jack (Output)	1 x 3.5mm Mini-Jack for External Speakers / Headphones	
Supported VGA Signals	Up to 1920 x 1080 @ 75Hz	
Mechanical Features		
Chassis Colors	Black	
Tilt	Backward: 15°, Forward: 5°	
Bezel Width	Top, Left and Right: 0.35" ; Bottom: 0.65"	
Neck / Stand Detachable	Yes	
Slim Design	Ultra Slim	
VESA Mount Pattern (mm)	100mm x 100mm	
VESA Mount Screw Size (mm)	M4 x 10mm	
Neck Screw Size & Quantity (mm)	M4*10mm 2pcs.	
Stand Screw Size & Quantity (mm)	M4*10mm 2pcs.	
Dimensions		
With Stand (inches, $W \times H \times D$)	24.46" x 17.75" x 9.05"	
Without Stand (Inches, W x H x D)	24.46" x 14.56" x 2.83"	
Carton Box Dimension (inches, W x H x I	D)26.81" x 17.91" x 4.68"	
Weight		
Net Weight with Stand (lbs)	8.55 lbs	
Net Weight without Stand (lbs)	7.58 lbs	
Gross Weight (lbs)	12.23 lbs	
Power		
Power Range (V, A, Hz)	AC Adapter	
	Input: 100 – 240V~ 50/60Hz, 1.2A	
	Output: 12V DC, 3.33A	
Power Consumption (Typical)	26 W	
	1	

SCEPTRE®		
Maximum	32W	
Standby	< 0.5W	
Regulations / Certifications		
Regulations	FCC, cTUVus, ISTA6A, HDMI	
Certifications	RoHS	
Warranty		
Limited Parts and Labor	One Year Limited Parts and Labor	
What's in the Box?		
Power Cable	AC Adapter x 1 (12V/3A)	
Display Cable	HDMI Cable x 1	
Accessories	Ultra Slim Monitor; Base x 1; Neck x 1; Base Screws x 1; Neck Screws x 2; Screwdriver x	
	1; User Manual x 1	



Key Features



Refresh Rate

Multiple Ports

sRGB



Multiple Monitors